Switch for blinds 10A 250V~ with 3 positions: up, down and stop white Simon 27 Play

REF. **27333-64**



BASIC INFORMATION

DESCRIPTION

The type is mechanical latching, it belongs to the Simon 27 Play range and in the categories of control of blinds, has a current of 10 A and a voltage of 250 V~ medium element and acomoda 3 positions: Raise, lower and stop, it also has a mechanism equipped with position control unit, i.e., allows you to stop the raising and lowering of the shutter. It has tilting operation and is suitable for 1 module, for its installation it will suffice to apply pressure or place on the surface. The wire section admitted is from 1.5 to 2.5 mm and has 11 mm of bare wire. The material is socket metal components with halogen-free thermoplastic insulation and thermoset trim, being able to oscillate between 5 and 40º, and can support up to a maximum of between -25 and 50º C, this article complies perfectly with the regulation EN 60669-1: 1999 + A1: 2002 + A2: 2008 + EN 50581: 2082. The dimensions are 22.5x45 mm, although it is available in other sizes and colors. To keep the piece clean, use a soft and dry cloth, under no circumstances be poured abrasive cloths or cleaners with high chlorine content.

FINISH

White

COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

PACKAGING CONTENTS

Mechanism with rocker

ETIM CLASS

EC000044

REMARKS

Mechanism with centre position to stop the up/down movement of the blinds.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

NUMBER OF POSSIBLE ELEMENTS

Half element

INDICATOR FUNCTION

No

CURRENT (A)

10 A

IP RATING

IP20

LATCH TYPE

Mechanical

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TYPE OF MECHANISM

Pivoting

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

VERSION

Single

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

11

CLAW

Simon 27

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, American, Small spaces and Centralisations

INSTALLATION TYPE

Suitable for surface and flush mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Fast

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD|Dir. 2011/65/UE RoHS + post. mod.|EN 60669-1:2018|EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053252000

UNITARY PACKAGING HEIGHT
22.8

UNITARY PACKAGING WIDTH
39.2

UNITARY PACKAGING LENGTH
46

UNITARY PACKAGING MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
0.041

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.03

PRODUCT NET WEIGHT
0.026

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053080825

UNITS CONTAINED PACKAGING
5

PACKAGING HEIGHT
55.5

PACKAGING WIDTH
54

PACKAGING LENGTH
131.8

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
0.395

PACKAGING VOLUME UNIT
DMQ

PACKAGING GROSS WEIGHT
0.15

PACKAGING NET WEIGHT
0.13

PACKAGING WEIGHT UNIT
KGM