

PD-25x3 Hallway HF+LUX BT Mesh surface BT-Slave white IP54

REF. 89215636-230



BASIC INFORMATION

DESCRIPTION

Surface presence and brightness detector HF. The recommended installation height is 2.8 m, with a maximum height of 4 m. It has a detection angle of 360° and an opening angle of 140°. The tangential detection range is 25 x 3 m and the radial detection range is 25 x 3 m.

The brightness regulation range is 2 - 2000 lux. The detector configuration is done via a bluetooth application.

Possibility of interconnection between sensors via Bluetooth. The control protocol is Bluetooth slave.

The power supply voltage is 220 - 240 VAC. The operating temperature of the detector is: -20 - 50 °C.

White finish, IP 54 protection rating, and dimensions: 123 x 123 x 62 mm.

5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL

PUSH BUTTON

No

ETIM CLASS

EC000133

COMPATIBILITY

Simon Sensor Pro

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

MAXIMUM POWER (W)

2000

RAL

9003

IP RATING

IP54

POWER SUPPLY (V~)

220/240 V~

CONTROL

Bluetooth Slave

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION
HEIGHT

2

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053357347

UNITARY PACKAGING GROSS
WEIGHT

0.378

PACKAGING LENGTH

143

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.272

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING VOLUME

2325323

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053357347

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING
MEASUREMENT UNIT

MMT

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.378

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

161

PACKAGING NET WEIGHT

0.272

UNITARY PACKAGING VOLUME
UNIT

MMQ

PACKAGING WIDTH

101

PACKAGING WEIGHT UNIT

KGM