

Complete kit with 4 schuko socket outlets and plate for 4 RJ45 connectors black S400 Top

REF. 42604040-138



BASIC INFORMATION

DESCRIPTION

Desk top kit, black in colour and belonging to the series Simon 400 Top. It has 4 Schuko socket outlets and plate for 4 RJ45 connectors. Its dimensions are 295 x 120 x 80 mm and it is of type manual elevation and its current is 16 A and works with a voltage of 250V. It supports a heat of over 70 and can be installed by flush mounted in furniture through the clamps that has pages. In the manufacture of this kit customizable required for the anodised aluminium profile, painted steel for the enclosure thermoplastic and halogen-free, self-extinguishing for the fastenings and covers. In terms of maintenance is very simple to perform since it will only need to use a soft and dry cloth, never resorting to the cloths or abrasive cleaners containing chlorine in its formulation, as it could be damaged.

FINISH

Black

MATERIAL

Metal

COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

PACKAGING CONTENTS

Pre-wired profile, table-top supports, rear trim cover and installation manual.

ETIM CLASS

EC002759

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60°C

FORMAT

Schuko

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

INSULATION RESISTANCE (V-MΩ)

>5 MΩ at 500 V

CURRENT (A)

16 A

IP RATING

IP30

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60°C

NOMINAL VOLTAGE (V~)

250 V~

TYPE OF POWER SUPPLY CONNECTOR

Wieland GST 18i male 3-pole overhead connector with 22 cm patch cord

RAL

9005

NUMBER OF RJ45 WINDOWS

4

SNAP-FIT RJ45 PLATES

Keystone I, II and Systimax

SNAP-FIT TYPE

Keystone I, II and Systimax

NUMBER OF SOCKETS

4 sockets for standard current circuit

VERSION

6 elements

INSTALLATION AND MAINTENANCE

CLAW RANGE OF OPERATION (MM)

Between 16 and 40 mm

EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

TYPE OF FASTENING

By tightening existing clamps in the fastening bracket.

INSTALLATION TYPE

Suitable for fixing to furniture.

SECURING POSSIBILITIES

Using clips included in the fastening brackets

MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053215913

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

1.075

PRODUCT NET WEIGHT

1.075

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053215913

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

95

PACKAGING WIDTH

125

PACKAGING LENGTH

330

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

3918750

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

1.075

PACKAGING WEIGHT UNIT

KGM