

818.22 1135mm surface 4000K Micro On-Off CRI80 White

REF. 81822030-684



BASIC INFORMATION

DESCRIPTION

818 individual linear LED luminaire suspendida mediante cables de acero, with extruded aluminium body y finished in negro. Length 1135 mm, equipada con diffuser microprismático y LED module with 4000K con CRI CRI80. Ofrece un luminous flux of 3550 lm con una power of 34W y an efficacy of 104 lm/W. Control On-Off, supply 220-240V, ideal for oficinas, comercios y indoor spaces where functional and efficient lighting is required.

MATERIAL

Aluminium

APPLICATION

General lighting

ETIM CLASS

EC002892

REMARKS

Includes installation accessories.

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IP RATING

IP20

OPERATING TEMPERATURE RANGE (°C)

0...+35

POWER SUPPLY (V~)

220/240 V~

CONTROL

On/Off

COLOR TYPE

NW

OPTICS

Microprismatic

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053376218

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

3.175

PRODUCT NET WEIGHT

2.69

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053376218

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

160

PACKAGING WIDTH

145

PACKAGING LENGTH

1145

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

26564000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

3.175

PACKAGING NET WEIGHT

2.69

PACKAGING WEIGHT UNIT

KGM