
Voice and data flat plate with dust cover for 1 element and 1 RJ45 connector category 6 FTP aluminium Simon K45

REF. **K96F/8**



BASIC INFORMATION

DESCRIPTION

Element of the plate and voice model K96F / 8 It is part of the range of components, for professional SimonK45 Connectors and plates for voice and data connections, easy combination with other elements Technical knowledge of the series. It is a plate of voice and Data flat plate with dust cover with 1 element for 1 RJ45 connector of Category 6 FTP and with snap-fit Keystone I, II, ATT ® / Avaya ® with insertion tool. Presents colour and finishes in tonality graphite, made with components Components with self-extinguishing and halogen-free thermoplastic insulation. That guarantees no flame propagation in case of fire and the low toxicity. In case of combination with plate of voice and Fatos vertical enclosures you need the element The 90º positioner (ref. K66) to a correct orientation. It has a Measures 45x45mm and a depth of 42,9mm, being very easy to To adapt to different systems and assemblies professionals, in different environments. Work professionals and home.

FINISH

Aluminium

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-033)

PACKAGING CONTENTS

Flat voice and data plate with dust cover, category 6 UTP RJ45 connector and installation manual

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90º positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
22-24 AWG wiring

RJ45 CONNECTION
With insertion tool

CONNECTOR CHARACTERISTICS
Category 6 FTP

RJ45 CONNECTORS
Included in voice and data plate

MAX TEMP DURING CONSTRUCTION WORK (ºC)
+60º C

DUST PROTECTION
Yes

FORMAT
RJ45

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (ºC)
-5 to 60º C

NUMBER OF MODULES
Half

PLATE TYPE
Flat

RJ45 ADAPTOR MODULE
Supplied with the voice and data plate

SNAP-FIT RJ45 PLATES
Keystone I, II, ATT®/Avaya®

SNAP-FIT TYPE
Keystone I, II, ATT®/Avaya®

VERSION
Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-033)

INSTALLATION DIRECTION
Vertical according to the direction of the mechanisms

INSTALLATION TYPE
Suitable for surface and flush mounting

REMOVAL OF THE PLATE
Only with tool

REGULATIONS

REGULATIONS
Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0.3

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.038

PRODUCT NET WEIGHT
0.038

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436046207

UNITS CONTAINED PACKAGING
10

PACKAGING HEIGHT
65

PACKAGING WIDTH
155

PACKAGING LENGTH
210

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
2115750

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.65

PACKAGING NET WEIGHT
0.38

PACKAGING WEIGHT UNIT
KGM