

USB charger (4.2 A) of 1 element K45 type "A+C" in graphite Simon K45

REF. K126G/14



BASIC INFORMATION

FINISH

Graphite

MATERIAL

Thermoplastic

COMPATIBILITY

It can only be used with structures for functions of the K45 family, except in watertight floor boxes IP66. The Simon 500 Cima to Simon K45 adapter is not compatible with this reference.

TECHNICAL INFORMATION

AVAILABLE MARKET CE	IP RATING IP20	RECESS DIMENSION (MM) 40
NUMBER OF CONNECTORS 2	MAINTENANCE Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.	USB CHARACTERISTICS 21W
CONNECTOR TYPE USB A + USB C		USB CURRENT (A) 4,2 A
NUMBER OF CONTACTS 2	NOMINAL VOLTAGE (V~) 230 V~	USB VOLTAGE (V~) 5 Vdc
FORMAT USB A + USB C	POWER SUPPLY (V~) 230 V~	NUMBER OF WIRES 2
INDICATOR FUNCTION Yes	RAL 7021	

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM) 10	EXTINGUISHING (°C) +850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-10-2)	TYPE OF TERMINAL CONNECTION - FUNCTION 1 Screw
REMOVAL OF CONNECTOR Only with tool	INSTALLATION DIRECTION Horizontal, Vertical	TYPE OF TERMINAL CONNECTION - FUNCTION 2 Screw

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053288412

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.082

PRODUCT NET WEIGHT

0.082

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053288412

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

56

PACKAGING WIDTH

15.5

PACKAGING LENGTH

78.5

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

68138

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

0.082

PACKAGING WEIGHT UNIT

KGM