

Downlight 800.24 White 35W 4000K DALI2

REF. 80024330-284



BASIC INFORMATION

APPLICATION

General technical lighting

PACKAGING CONTENTS

1 Units

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

CRI

80

LUMENS/W

3400 lm/35W

IP RATING

IP54

ELECTRICAL CLASS

tipo 2

OPTICS

Closed

OPERATING TEMPERATURE RANGE (°C)

-15°C a 35°C

L70 (°C)

50.000 h a 25°C

PHOTOBIOLOGICAL CLASSIFICATION

Categoría exento

POWER SUPPLY (V~)

220/240 V~

LIGHT BEAM APERTURE ANGLE (°)

24°

POWER (W)

35W

COLOR TEMPERATURE (K)

4000K

COLOR TYPE

NW

SERVICE LIFE

50.000 h

CONTROL

DALI2

LIGHTING EFFICIENCY (LM/W)

100 lm/W

COS Φ

0.95

LUMENS (LM)

3400 lm

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

130

INSTALLATION TYPE

Recessed

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Quick connector

REGULATIONS

WARRANTY

5 years 50.000 h

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053304563

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053304563

PACKAGING VOLUME

7793750

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

145

PACKAGING GROSS WEIGHT

1.192

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

250

PACKAGING NET WEIGHT

0.974

UNITARY PACKAGING GROSS
WEIGHT

0.974

PACKAGING LENGTH

215

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.974