

Aluminum profile Ofiblock Line with 1 element and 2 rear wiring accesses black Simon K45

REF. KFC231/14



BASIC INFORMATION

FINISH

Black

MATERIAL

Metal, Plastic

COMPATIBILITY

Functions of the Simon K45 range and combinable with the Simon Electrical Wiring range.

ETIM CLASS

EC002759

TECHNICAL INFORMATION

HEAT RESISTANCE (°C)

+125°C (according to standard IEC 60670)

IP RATING

IP4X

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MONOBLOCK

No

RAL

7021

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

EXTINGUISHING (°C)

+850 °C (according to standard IEC 60670)

INSTALLATION DIRECTION

Horizontal, Vertical

SECURING POSSIBILITIES

Its design allows it to be surface-mounted on the wall, on table-top furniture, under a desk, on a raised floor, a metal surface with magnet, or on a DIN rail using specific fastening accessories.

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053305669

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.38

PRODUCT NET WEIGHT

0.38

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053305669

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

59.5

PACKAGING WIDTH

105

PACKAGING LENGTH

54.5

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

911400

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.411

PACKAGING NET WEIGHT

0.38

PACKAGING WEIGHT UNIT

KGM