

Modular luminaire 726 60x60 Low Glare WW

REF. 72660033-683



BASIC INFORMATION

DESCRIPTION

This is the luminaire 726 modular 60 x 60 LowGlare with LEDs in warm colour (WW). It is a product specific for indoor lighting of the series of Simon 726 modular luminaires. It is category B and its quality is excellent. The finish of the luminaire is an aluminium colour, very versatile, which allows it to be incorporate into everyday in any space. It has an optimal microprismatic and its temperature of the colour is 3000 K. It has 2900 lumens and a power 39 W the power supply of the luminaire is 220-240 V and has a frequency of 50-60 Hz. The electric control of the product is carried out from the simple system of ON-OFF, as well as providing maximum functionality. The total luminaire weight of this Simon is 2,6 kilos and its dimensions are 595 millimetres. Its installation must be done in false ceiling, with the hardware. It also withstands temperatures very variables, from the most low to the highest.

DIFFUSER MATERIAL

PMMA

APPLICATION

General lighting

PACKAGING CONTENTS

1 unit

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LUMENS (LM)

2900 lm

IP RATING

IP20

ELECTRICAL CLASS

Tipo 2

LUMENS/W

2900 lm/39W

OPERATING TEMPERATURE RANGE (°C)

-15 - 40 °C

INTEGRATED POWER SUPPLY

No

OPTICS

Microprismatic

POWER SUPPLY (V~)

220/240 V~

L70 (°C)

30,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempted category

COLOR TEMPERATURE (K)

3000 K

LIGHT BEAM APERTURE ANGLE (°)

90°

POWER (W)

39 W

CONTROL

On/Off

COLOR TYPE

WW

SERVICE LIFE

30.000 h

CRI

80

LIGHTING EFFICIENCY (LM/W)

74 lm/W

CHROMATICS CRI ICONS

CRI
80

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Plaster ceiling, surface mount, flush mount, concealed profile and suspended

MINIMUM INSTALLATION HEIGHT

250

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

INSTALLATION TYPE

False ceiling, visible hardware

REGULATIONS

WARRANTY

3 years 30,000 h

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

3

PRODUCT NET WEIGHT

2.1

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053193846

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

55

PACKAGING WIDTH

725

PACKAGING LENGTH

650

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

25918750

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

3

PACKAGING NET WEIGHT

2.1

PACKAGING WEIGHT UNIT

KGM