

## Luminaire HOLE 50 Flush mount 2700K Flood White CRI98

REF. 91411932-200



### BASIC INFORMATION

#### FINISH

White

#### PACKAGING CONTENTS

1 unit

#### APPLICATION

Flush mount

#### ETIM CLASS

EC001744

## TECHNICAL INFORMATION

### FREQUENCY

50 - 60 Hz

### CRI

90

### LUMENS (LM)

254 lm

### IP RATING

IP20

### DRIVER INCLUDED

No

### LUMENS/W

254

### OPERATING TEMPERATURE RANGE (°C)

0 - 35 °C

### ELECTRICAL CLASS

Type 3

### MACADAM STEPS

<3 Step MacAdam

### POWER SUPPLY (V~)

33 V~

### L70 (°C)

150.000h at 25°C

### OPTICS

Flood 35°

### RAL

9016

### L90 (°C)

40.000h at 25°C

### POWER (W)

3.5 W

### COLOR TEMPERATURE (K)

2700 K

### LIGHTING EFFICIENCY (LM/W)

103 lm/W

### SERVICE LIFE

50.000 h

## INSTALLATION AND MAINTENANCE

### INSTALLATION TYPE

Flush mount

## REGULATIONS

### EAC MARKED

Yes

### WARRANTY

5 years

## LOGISTICS INFORMATION

UNITARY EAN CODE

8436547055524

UNITARY PACKAGING WEIGHT  
UNIT

KGM

PACKAGING MEASUREMENT  
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8436547055524

PACKAGING VOLUME

4083200

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

80

PACKAGING GROSS WEIGHT

0.432

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

176

PACKAGING NET WEIGHT

0.432

UNITARY PACKAGING GROSS  
WEIGHT

0.432

PACKAGING LENGTH

290

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.432