


Set of 2 disconnect push-button switches 10A 250V~ (circuit opens when pressed) with fast terminal connection system

REF. 75395-39



BASIC INFORMATION

DESCRIPTION

Unit of 2 shutdown push buttons 10A 250V~ with quick terminal connection system. It has a rocker operation, which means that when pressed opens the circuit. This mechanism is included in the Simon 75 series and has been manufactured in strict compliance with the current regulation. It is a product suitable for surface or flush mounting installation. The socket is made of metal components with halogen-free thermoplastic insulation, a material that guarantees maximum protection and security in all kinds of environments, the article has the ability to withstand even the most extreme temperatures, although the ideal thing is to install it in spaces whose temperature ranges between 5 and 40°C. The Simon 75 series stands out for its wide range of mechanisms suitable for any ambience. Moreover, its products are compatible with the Simon 77 series.

COMPATIBILITY

Simon 75, Simon 82 Detail, Simon 82 Nature, Simon 82 and Simon 88 frames

PACKAGING CONTENTS

Mechanism

ETIM CLASS

EC000029

REMARKS

Disconnect push button. Pressing opens circuit.

TECHNICAL INFORMATION

CABLE SECTION ADMITTED (MM) From 1,5 to 2,5 mm	IP RATING IP21	STORAGE TEMPERATURE RANGE (°C) -25 - 50 °C
NUMBER OF POSSIBLE ELEMENTS 1 element	TYPE OF MECHANISM Pivoting	VERSION Double
INDICATOR FUNCTION No	OPERATING TEMPERATURE RANGE (°C) 5 - 40 °C	VOLTAGE (V~) 250 V~
CURRENT (A) 10 A		

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM) 11	INSTALLABLE IN FLUSH MOUNT JUNCTION BOX Universal	TYPE OF TERMINAL CONNECTION - FUNCTION 1 Fast
CLAW Simon 27	INSTALLATION TYPE Suitable for surface and flush mounting	

REGULATIONS

REGULATIONS


Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN 60669-1:2018 | EN IEC 63000:2018

LOGISTICS INFORMATION


UNITARY EAN CODE 8421053256008	UNITARY PACKAGING GROSS WEIGHT 0.075	PACKAGING LENGTH 221
UNITARY PACKAGING HEIGHT 0	PRODUCT NET WEIGHT 0.075	PACKAGING MEASUREMENT UNIT MMT
UNITARY PACKAGING WIDTH 0	UNITARY PACKAGING WEIGHT UNIT KGM	PACKAGING VOLUME 3026595
UNITARY PACKAGING LENGTH 0	PACKAGING EAN 8421053017548	PACKAGING VOLUME UNIT MMQ
UNITARY PACKAGING MEASUREMENT UNIT MMT	UNITS CONTAINED PACKAGING 10	PACKAGING GROSS WEIGHT 0.75
UNITARY PACKAGING VOLUME 3026595	PACKAGING HEIGHT 83	PACKAGING NET WEIGHT 0.75
UNITARY PACKAGING VOLUME UNIT MMQ	PACKAGING WIDTH 165	PACKAGING WEIGHT UNIT KGM

MECANISMOS SIMON 31, 75, 77, 82 Y 88


Mecanismos básicos / Basic switches




Interruptor unipolar / Single-pole switch
XXXX101-XXX




Interruptor unipolar / Single-pole switch
7700101-039




Pulsador / Push button switch
XXXX150-XXX




Pulsador / Push button switch
7700150-039




Interruptor bipolar / Double pole switch
XXXX133-XXX




Conmutador / 2-way switch
XXXX201-XXX




Conmutador / 2-way switch
7700201-039




Conmutador cruce / Intermediate switch
XXXX251-XXX




Conmutador cruce / Intermediate switch
7700251-039




Grupo 2 interruptores / 2 switches group
XXXX398-XXX




Pulsador desconexión / Push button disconnection switch
XXXX152-XXX




Grupo dos conmutadores / 2-way switches group
XXXX397-XXX




Grupo de pulsadores desconexión / Push button switch disconnection group
XXXX395-XXX




Grupo conmutador y pulsador / 2-way and push button switch group
XXXX301-XXX




Interruptor unipolar / Single-pole switch
XXXX102-XXX




Interruptor con piloto / Push button pilot switch
7700112-039




Interruptor bipolar / Double pole switch
XXXX134-XXX




Conmutador / 2-way switch
XXXX202-XXX




Interrupor unipolar con luminoso / Single-pole switch with light
XXXX104-XXX




Pulsador con luminoso / Push button switch with light
XXXX160-XXX



Pulsador con luminoso / Push button switch with light
7700160-039



Conmutador con luminoso / 2-way switch with light
XXXX204-XXX



Conmutador cruce con luminoso / Intermediate switch with light
XXXX254-XXX