Reduced depth floor box with 3 double elements for installation in technical or pavement floor gray Simon Cima

REF. **SF300C/1**



BASIC INFORMATION

FINISH
Grey

MATERIAL
Various

COMPATIBILITY
With mechanisms Simon Series S and Simon 25 / Simon K45 (via adapter)

ETIM CLASS
EC000024

TECHNICAL INFORMATION

NUMBER OF CLAMP-HOLDER HOLES
6

HEAT RESISTANCE (°C)
+125 °C (in accordance with standard IEC 60695-10-2)

IK CLASSIFICATION
08

KIT AVAILABILITY
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MAXIMUM LOAD (KG)
790kg

NUMBER OF PRE-PUNCHED HOLES 55 X 20 MM
6

RAL
7011

RECESS DIMENSION (MM)
Ø 300 mm

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS
Only with tool

NUMBER OF COVER OPENING POSITIONS
3

EXTINGUISHING (°C)
+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

REMOVAL OF THE FRAME
Only with tool

CAN BE INSTALLED IN TRAY
Plástica

LOGISTICS INFORMATION

UNITARY EAN CODE
8426436050877

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0.3

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
2.03

PRODUCT NET WEIGHT
2.03

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436050877

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
80

PACKAGING WIDTH
325

PACKAGING LENGTH
325

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
8.45

PACKAGING VOLUME UNIT
DMQ

PACKAGING GROSS WEIGHT
2.02

PACKAGING NET WEIGHT
2.03

PACKAGING WEIGHT UNIT
KGM