Complete set with 2 schuko socket outlets, 2 UPS sockets and plate for 4 RJ45 connectors black S400 Top

REF. **42602240-138**



BASIC INFORMATION

DESCRIPTION

Enjoyment of the highest quality in its connections for its work area kit desk top of the collection Simon 400 Top. With 2 Schuko socket outlets, 2 with power uninterrupted (UPS/UPS (uninterruptable power supplies)) and plate for 4 RJ45 connectors, your workplace, gozar® of maximum functionality and innovation in the minimum space. With finishes in black and a compact dimension of 295 x 120 x 80 mm, this kit is integrated into all types of decorative spaces and environments, in addition, thanks to its installation, flush mounted. Compatible with a voltage of 250 V of power and 16 A of intensity, is connected to figure Wieland gst 18 i with 3-pole male and 22 cm of patch cord. It has a dielectric strength, with no holes or contours, 2000 V at 50H during 1 minute, and insulation resistance > 5 M? at 500 V. Made of anodised aluminium and thermoplastic self-extinguishing halogen-free, protects the room in case of fire, as it avoids the flame spread and toxicity by smoke.

FINISH

Black

MATERIAL

Metal

COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

PACKAGING CONTENTS

Pre-wired profile, table-top supports, rear trim cover and installation manual.

ETIM CLASS

EC002759

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

DIELECTRIC STRENGTH
No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60°C

FORMAT
Schuko

HEAT RESISTANCE (°C)
+70°C (according to standard IEC 60670)

INSULATION RESISTANCE (V-MΩ)
>5 M? at 500 V

CURRENT (A)
16 A

IP RATING
IP30

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 at +60° C

NOMINAL VOLTAGE (V~)
250 V~

TYPE OF POWER SUPPLY CONNECTOR
Wieland® GST 18i male 3-pole overhead connector with 22 cm patch cord

RAL
9005

NUMBER OF RJ45 WINDOWS
4

SNAP-FIT RJ45 PLATES
Keystone® I, II and Systimax®

SNAP-FIT TYPE
Keystone® I, II and Systimax®

NUMBER OF SOCKETS
2 sockets for standard current circuit and 2 sockets for stable current circuit (UPS)

NUMBER OF UPS SOCKET OUTLETS
2

VERSION
6 elements

INSTALLATION AND MAINTENANCE

CLAW RANGE OF OPERATION (MM)
Between 16 and 40 mm

EXTINGUISHING (°C)
+70 °C (according to standard IEC 60670)

TYPE OF FASTENING
By tightening existing clamps in the fastening bracket.

INSTALLATION TYPE
Suitable for fixing to furniture.

SECURING POSSIBILITIES
Using clips included in the fastening brackets

MOUNTING WITHOUT ACCESSORIES
Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50173-1:2011;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053196069

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
1.2

PRODUCT NET WEIGHT
1.2

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053196069

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
330

PACKAGING WIDTH
125

PACKAGING LENGTH
95

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
3918750

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
1.2

PACKAGING WEIGHT UNIT
KGM