
Voice and data flat plate without dust cover for 1 element with 2 RJ45 connectors category 6 FTP white Simon K45

REF. **KB096F/9**



BASIC INFORMATION

DESCRIPTION

Voice and data flat plate with 1 element and 2 RJ45 category 6 FTP connectors in the collection Simon K45 with a soft finishes white in colour, it is the solution for the most electromagnetic compatibility, on the market. Its direct snap-fit RJ45 ports type is compatible with Keystone and accepted connection of cabling 22-24 AWG. Made of halogen-free, self-extinguishing thermoplastic prevents the flame spread and toxicity by smoke in case of fire. Designed for installation both recessed and surface-mounted, does not require tools screws, making it easier and minimizing the time of installation and maximizing its functionality. In case of combining it in vertical enclosures, requires the 90 ° positioner (ref.K66) to guide the plate and adapt it to the space in question. The flat base plate of voice and data K45, it is compatible with all types of connections on the market strengthening its functionality, innovation and quality assurance of the collection Simon K45.

FINISH

White

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

Voice and data flat plate without dust cover, RJ45 category 6 FTP connectors

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90º positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
22-24 AWG wiring

RJ45 CONNECTION
With insertion tool

CONNECTOR CHARACTERISTICS
Category 6 FTP

RJ45 CONNECTORS
Included in voice and data plate

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60° C

DUST PROTECTION
No

FORMAT
RJ45

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60° C

NUMBER OF MODULES
Half

PLATE TYPE
Flat

RAL
9003

RJ45 ADAPTOR MODULE
Included in voice and data plate

SNAP-FIT RJ45 PLATES
Keystone I, II, ATT®/Avaya®

SNAP-FIT TYPE
Keystone I, II, ATT®/Avaya®

VERSION
Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

INSTALLATION DIRECTION
Vertical according to the direction of the mechanisms

INSTALLATION TYPE
Suitable for surface and flush mounting

REMOVAL OF THE PLATE
Only with tool

REGULATIONS

REGULATIONS
Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.045

PRODUCT NET WEIGHT
0.045

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436047945

UNITS CONTAINED PACKAGING
10

PACKAGING HEIGHT
112

PACKAGING WIDTH
117

PACKAGING LENGTH
269

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
3.525

PACKAGING VOLUME UNIT
DMQ

PACKAGING GROSS WEIGHT
0.45

PACKAGING NET WEIGHT
0.45

PACKAGING WEIGHT UNIT
KGM