

**Neutral push-button switch 10A 250V~ for half element
with built-in light indicator and fast terminal connection
system white Simon 27 Play**

REF. 27669-64



BASIC INFORMATION

DESCRIPTION

Create the ideal atmosphere for your home or business is possible thanks to the wide range of colours of the Simon 27 Play series. The qualities of this range are present in the neutral ush-button switch 10A 250V~, half element, with pilot and fast-terminals connection in white. This is a tilting push-button switch with dimensions of 22.5x45 mm, a wire cross section of 1.5 to 2.5 mm, a signal consumption of 0.55 mA and a wire stripping of 11 mm, it also, it can be combined with the reference 2700802-064 in case of replacement of the indicator light, it has been manufactured with metal components with halogen-free insulation and thermoset trim, being suitable for surface and flush mounting. Its low price makes it affordable to all types of budgets both in new construction and refurbishment of homes and buildings.

FINISH

White

COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

PACKAGING CONTENTS

Mechanism with rocker

ETIM CLASS

EC000029

REMARKS

Can be combined with article 2700802-064 if replacing the light indicator.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

INDICATOR FUNCTION

Yes

TYPE OF MECHANISM

Pivoting

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

IP RATING

IP20

NOMINAL VOLTAGE (V~)

250 V~

CONSUMPTION INDICATOR (mA)

0.55 mA

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

NUMBER OF POSSIBLE ELEMENTS

Half element

VERSION

Single

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

11

CLAW

Simon 27

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, American, Small
spaces and Centralisations

INSTALLATION DIRECTION

Horizontal, Vertical

INSTALLATION TYPE

Suitable for surface and flush
mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Fast

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN 60669-1:2018 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053252659

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

1229865

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.024

PRODUCT NET WEIGHT

0.024

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053051016

UNITS CONTAINED PACKAGING

20

PACKAGING HEIGHT

53

PACKAGING WIDTH

105

PACKAGING LENGTH

221

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1229865

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.475

PACKAGING NET WEIGHT

0.48

PACKAGING WEIGHT UNIT

KGM