Flush-mount trim cover circular shallow floor box for 6 elements grey Simon 500 Cima

REF. **52053203-035**



BASIC INFORMATION

DESCRIPTION

Component of the box Circular model 52053203-035 belonging to the range of products professionals Simon 500 Cima, with capacity for easy combination with other elements of The Simon 500 Cima range is an element, designed to facilitate the installation In flush mounted in concrete floor and raised floor. Trim cover for Flush-mounted floor box for shallow circular, version for 6 Elements, manufactured in plastic material and with finishes in tonality and Grey colour. Integrated components of character halogen-free thermoplastic That guarantees no flame propagation in case of fire and the low Toxicity in case of smoke. Component is ideal for All types of installations and systems professionals assembly, with dimensions of Ø 244 mm x 5 mm, ideal for endorse an element essential to have in Concrete floor and raised floor.

FINISH

Grey

PACKAGING CONTENTS

Trim cover

MATERIAL

Plastic

ETIM CLASS

EC002417

REMARKS

Optional element. To combine with the floor box if not installing the same floor finish.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

AVAILABLE IN
4, 6 and 8 elements

DIELECTRIC STRENGTH
No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (ºC)
+90 ºC

HEAT RESISTANCE (ºC)
+125ºC (according rule IEC 60695-10-2)

IK CLASSIFICATION
08

INSULATION RESISTANCE (V-MΩ)
>5 MOhms at 500V

IP RATING
IP4X

KIT AVAILABILITY
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (ºC)
-5 to 60 ºC

NUMBER OF MODULES
6 modules

RAL
7011

VERSION
6 elements

INSTALLATION AND MAINTENANCE

REMOVAL OF COVER
Only with tool

EXTINGUISHING (ºC)
+850 ºC / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

TYPE OF FASTENING
Using the screws supplied

INSTALLATION DIRECTION
Circular, in line with the installation of the floor box

INSTALLATION TYPE
In raised or concrete floor with shallow floor boxes

REGULATIONS

REGULATIONS
Directive 2014/35/UE LVD + EN 60670-23:2008

LOGISTICS INFORMATION

UNITARY EAN CODE
84210531016810

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.145

PRODUCT NET WEIGHT
0.145

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
84210531016810

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
5

PACKAGING WIDTH
370

PACKAGING LENGTH
245

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
453250

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
0.145

PACKAGING WEIGHT UNIT
KGM