

Angled voice and data plate with dust cover for 1 element with 1 RJ45 category 6 FTP white Simon 500 Cima

REF. 50003081-030



BASIC INFORMATION

DESCRIPTION

In the Simon 500 Cima series we find a great catalogue of connectors and plates for voice and data connections. This is the plate of voice and data plate, an element with an RJ45 connector. Includes a dust shutter and is category 6 FTP. The product is presented in a versatile finished in white colour. Its snap-fit is performed by Keystone I, II, ATT, Avaya. This is the individual version, a module, the plate Simon. The clips for the fastening of the same in horizontal or vertical enclosures are included. Therefore, it is not necessary to the use of adaptors. With measures of 50 x 50 millimetres and a depth of 55,4 millimetres, this plate Simon supports a cabling 22-26 AWG. It is manufactured with metallic components isolated thermoplastically. Does not contain halogens, so that the power security and the versatility of use. You just need to clean it with a soft cotton completely dry cloth.

FINISH

White

PACKAGING CONTENTS

Angled voice and data plate with dust cover, RJ45 category 6 FTP connector and installation manual

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

NUMBER OF MODULES

1

CABLE SECTION ADMITTED (MM)

22-26 AWG wiring

DUST SHUTTER

Yes

PLATE TYPE

Angled

AVAILABLE IN

Plate for 1 and 2 RJ45

FORMAT

RJ45

RAL

9003

RJ45 CONNECTION

Without insertion tool

IP RATING

IP20

RJ45 ADAPTOR MODULE

Included in voice and data plate

CONNECTOR CHARACTERISTICS

category 6 FTP

KIT AVAILABILITY

No

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

NUMBER OF CONNECTORS

1

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

VERSION

Single

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

INSTALLATION AND MAINTENANCE

REMOVAL OF CONNECTOR

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053097762

PACKAGING VOLUME

0.052

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

20

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

80

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS WEIGHT

0.08

PACKAGING WIDTH

224

PACKAGING NET WEIGHT

1.6

PRODUCT NET WEIGHT

0.08

PACKAGING LENGTH

290

PACKAGING WEIGHT UNIT

KGM

