Trim plate for 1 quick connection connector with 3 poles male or female for 1 element black Simon K45

REF. **K18/14**



BASIC INFORMATION

DESCRIPTION

Suitable for both surface-mounted and to be recessed and with an elegant finishes in black, our trim plate for one 3-pole quick connection connector is part of the collection Simon K45 to choose between male or female, its dimensions are 45x45x8,5 mm and is manufactured in halogen-free thermoplastic material to be able to ensure that the fire is not propagate if had fire, in addition to a minimum toxicity in the event of smoke generation. Although the piece does not include the connector, you can choose from other brands of fast-connection connectors, since our plate is compatible with the leading manufacturers. The only thing is required for proper fastening the connector is that the clips have between 1.5 and 2 mm in thickness. And it is that the collection Simon K45 has been specially designed to fall in love up to the most demanding clients, as it brings together all types of mechanisms self-extinguishing to be able to enjoy a total security. This is why our commitment by reinventarnos every day you Patent in each and every one of our collections.

FINISH

Black

MATERIAL

Plastic

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-038)

PACKAGING CONTENTS

Plate for one 3-pole quick connection connector

ETIM CLASS

EC000011

REMARKS

Connector not included (to be purchased separately). If using another quick connect brand, the plate is compatible with the leading manufacturers (Wieland®, Wago®, etc). To fix the connector to the plate correctly, the clips must be between 1.5 and 2 mm thick.

TECHNICAL INFORMATION

AVAILABLE IN
Versions for 1 and 2 quick-connection connectors with 3 male or female poles

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60° C

FORMAT
GST18

INDICATOR FUNCTION
No

IP RATING
IP20

KIT AVAILABILITY
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60° C

NUMBER OF MODULES
Half

RAL
7021

VERSION
Single

INSTALLATION AND MAINTENANCE

TYPE OF FASTENING
Fixing by direct snap-fit, no tools needed

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-038)

INSTALLATION DIRECTION
Vertical according to the direction of the mechanisms

INSTALLATION TYPE
Suitable for surface and flush mounting

REMOVAL OF THE PLATE
Only with tool

REGULATIONS

REGULATIONS
Directive 2014/35/UE LVD + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60535:2009 A1:2013

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0.3

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.009

PRODUCT NET WEIGHT
0.009

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436036703

UNITS CONTAINED PACKAGING
20

PACKAGING HEIGHT
70

PACKAGING WIDTH
93

PACKAGING LENGTH
140

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
911400

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.18

PACKAGING NET WEIGHT
0.18

PACKAGING WEIGHT UNIT
KGM