Modular Luminaire 730 120x10 3000 K General 1-10 V

REF. **73062140-883**

BASIC INFORMATION

DESCRIPTION

This versatile linear luminaire offered by Simon has a high efficiency and light quality. Thanks to its design and its small weight, it can be installed easily and with its warm light allows to create comfortable work spaces.

It has IP 44 protection and its optics offers a light beam aperture angle of 100 degrees. It stands out for its long service life, along with a 5 year guarantee.

APPLICATION

General lighting

PACKAGING CONTENTS

1 unit

TECHNICAL INFORMATION

FREQUENCY
50 - 60 Hz

IP RATING
IP44

OPERATING TEMPERATURE RANGE (ºC)
40 ºC maximum

POWER SUPPLY (V~)
230 V~

COLOR TEMPERATURE (K)
3000 K

CONTROL
1-10 V

CRI
80

CHROMATICS CRI ICONS

DIRECTIONAL
No

DRIVER INCLUDED
Yes

L70 (ºC)
100.000 h at 25ºC

L90 (ºC)
50.000 h at 25ºC

LIGHT BEAM APERTURE ANGLE (°)
100º

COLOR TYPE
WW

LIGHTING EFFICIENCY (LM/W)
99 lm/W

LUMENS (LM)
3400 lm

LUMENS/W
3400lm/ 34,5W

OPTICS
General

PHOTOBIOLOGICAL CLASSIFICATION
Exempt category

POWER (W)
34.5 W

SERVICE LIFE
50.000 h

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES
Surface-mounted, Concealed ceiling, Semi-concealed ceiling, Flush-mounted

INSTALLATION TYPE
False ceiling, visible hardware

REGULATIONS

WARRANTY
5 years

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053204368

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
3.1

PRODUCT NET WEIGHT
2.8

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053204368

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
87

PACKAGING WIDTH
110

PACKAGING LENGTH
1215

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
11627550

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
3.1

PACKAGING NET WEIGHT
2.8

PACKAGING WEIGHT UNIT
KGM