

Downlight 725.22 Flush mount WW General IP44 Aluminium

REF. 72522933-983



BASIC INFORMATION

APPLICATION

General lighting

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY (HZ)

50 - 60 Hz

DRIVER INCLUDED

Yes

LUMENS (LM)

2100 lm

IP RATING

IP44

ELECTRICAL CLASS

Type 1

LUMENS/W

2100 lm/24W

OPERATING TEMPERATURE RANGE (°C)

-15 - 40 °C

INTEGRATED POWER SUPPLY

Yes

OPTICS

General

POWER SUPPLY (V~)

100/240 V~

L70 (°C)

30,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

COLOR TEMPERATURE (K)

3100 K

LIGHT BEAM APERTURE ANGLE (°)

120°

POWER (W)

24 W

CONTROL

On/Off

COLOR TYPE

WW

SERVICE LIFE

30.000 h

CRI

80

LIGHTING EFFICIENCY (LM/W)

88 lm/W

CHROMATICS CRI ICONS

CRI
80

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Surface

INSTALLATION TYPE

Flush mount

MINIMUM INSTALLATION HEIGHT

107

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Quick connector

REGULATIONS

WARRANTY

3 years 30,000 h

LOGISTICS INFORMATION

UNITARY PACKAGING GROSS WEIGHT

1.442

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING LENGTH

0

PRODUCT NET WEIGHT

1.442

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053116784

PACKAGING GROSS WEIGHT

0

PACKAGING HEIGHT

70

PACKAGING LENGTH

245

PACKAGING NET WEIGHT

1.442

UNITS CONTAINED PACKAGING

1

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

0.042

PACKAGING VOLUME UNIT

HLT

PACKAGING WEIGHT UNIT

KGM

PACKAGING WIDTH

245