

Voice and data angled plate with dust cover for 1 element and 1 RJ45 connector category 5e FTP black Simon K45

REF. K8095F/14



BASIC INFORMATION

DESCRIPTION

The plate of voice and data tilted plate with dust cover for an element of the collection Simon K45, is the solution to ensure the electromagnetic compatibility, total that demand the market thanks to its RJ45 connector of category 5e FTP. With elegant and discreet finishes in black, the angled voice and data plate K45, is made up of self-extinguishing halogen-free thermoplastic to protect your room of the flame spread and smoke fire. With a discrete design, its installation does not require tools screws and guarantees, in addition, an optimal bending radius in the data installations. The RJ45 connector is clipped directly to the plate, but its assembly requires the module multimedia (MD) corresponding to ensure maximum functionality. With a temperature range of installation of between -5°C and 60 ° C, the plate of voice and data tilted plate Simon K45, suitable for installation in surface-mounted or recessed, gives the product versatility, functionality and innovation.

FINISH

Black

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-038)

PACKAGING CONTENTS

Angled voice and data plate with dust cover, direct module for snap-fit connector, RJ45 category 5e UTP connector and installation manual

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90° positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

NUMBER OF MODULES

Half

CABLE SECTION ADMITTED (MM)

22-24 AWG wiring

DUST SHUTTER

Yes

PLATE TYPE

Angled

AVAILABLE IN

Plate with 1 RJ45 connector

FORMAT

RJ45

RAL

7021

RJ45 CONNECTION

With insertion tool

IP RATING

IP20

RJ45 ADAPTOR MODULE

Supplied with the voice and data plate

CONNECTOR CHARACTERISTICS

Category 5e FTP

KIT AVAILABILITY

No

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

VERSION

Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-038)

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

INSTALLATION TYPE

Suitable for surface and flush mounting

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.033

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

2871375

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436040298

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0.3

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0.26

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING HEIGHT

95

PACKAGING NET WEIGHT

0.33

UNITARY PACKAGING GROSS WEIGHT

0.033

PACKAGING WIDTH

155

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

195