

## Customisable set with 1 schuko socket outlet and 3 empty elements black S400 Top

REF. 42401000-138



## BASIC INFORMATION

### DESCRIPTION

Adapting to the needs of the new technical work spaces, the kit of desk top customizable of Simon 400 Top, coupled in a single space, all the electrical functions and connection that requires the environment. With 1 Schuko socket-outlet empty and 3 elements, this kit adapts to the space to the needs eliminate tables and desks, and providing more amplitude and greater functionality. With a design of simple lines and finishes in black, has a dimension of 205 x 120 x 80 mm and is designed for flush installation in furniture, without the need to use additional tools. It is compatible with a voltage of 250 V, and 16 A of intensity, and its power supply is connected to figure Wieland gst 18i with 3-pole male in-line and patch cord of 22 cm, it also has a insulation resistance > 5 M $\Omega$  at 500 V, and 2000 V at 50H / minute of dielectric strength.

### FINISH

Black

### MATERIAL

Metal

### COMPATIBILITY

Functions of the Simon 400 range, combinable with the Simon Electric Cabling range.

### PACKAGING CONTENTS

Pre-wired profile, table-top supports, rear trim cover and installation manual.

### ETIM CLASS

EC002759

### REMARKS

To complete the product installation combine it with the Simon 400 functions (refs. 400XXXXX-03X).

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

### MAX TEMP DURING CONSTRUCTION WORK (°C)

+60°C

### NUMBER OF POSSIBLE ELEMENTS

3

### FORMAT

Schuko

### HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

### INSULATION RESISTANCE (V-MΩ)

>5 MΩ at 500 V

### CURRENT (A)

16 A

### IP RATING

IP30

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60°C

### NOMINAL VOLTAGE (V~)

250 V~

### TYPE OF POWER SUPPLY CONNECTOR

Wieland GST 18i male 3-pole overhead connector with 22 cm patch cord

### RAL

9005

### NUMBER OF REAR ENTRANCES

3

### NUMBER OF SOCKETS

1 socket for standard current circuit

### VERSION

4 elements

## INSTALLATION AND MAINTENANCE

### CLAW RANGE OF OPERATION (MM)

Between 16 and 40 mm

### REMOVAL OF COMPONENTS

### EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

### TYPE OF FASTENING

By tightening existing clamps in the fastening bracket.

### INSTALLATION TYPE

Suitable for fixing to furniture.

### REMOVAL OF THE PLATE

Only with tool

### SECURING POSSIBILITIES

Using clips included in the fastening brackets

### MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

## REGULATIONS

### REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053195611

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING GROSS WEIGHT

0.82

### PRODUCT NET WEIGHT

0.82

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053195611

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

240

### PACKAGING WIDTH

125

### PACKAGING LENGTH

95

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

2850000

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0

### PACKAGING NET WEIGHT

0.82

### PACKAGING WEIGHT UNIT

KGM