Extension 0.5 metres for aluminium column with 2 sides Simon 500 Cima

REF. **53555201-033**



BASIC INFORMATION

DESCRIPTION

Extension of 0.50 meters for pole of aluminium of 2 sides of the Simon 500 Cima series. Is fixed to the ceiling and has dimensions of 500 x 110 mm x 127 It is made of anodised aluminium and has been designed according to UNE -s 50.085-2-4-: 2006 and its fastening is calculated using a telescopic guide attached to the ceiling slab. It can be installed in any room with a temperature located between -25 and 60 ° C, approximately, so it is a perfect extension for use in any type of climatology. To clean it, you will not need anything that a dry and soft cloth and forget you to use any type of a cloth and / or abrasive cleaners containing any index chlorine among its components.

FINISH

Aluminium

MATERIAL

Aluminium

COMPATIBILITY

Simon 500 Cima, Simon 27 Play/Simon K45 (using adaptor) mechanisms and universal Simon mechanisms in combination with the universal box designed specifically for columns.

PACKAGING CONTENTS

Extension and installation manual

ETIM CLASS

EC000795

REMARKS

To ensure the robustness of the total structure, it is only possible to combine one extension per column

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

AVAILABLE IN

1 and 2 sides

MAX TEMP DURING CONSTRUCTION WORK (ºC)

+120 ºC

EARTHING RESISTANCE

< 0.05 Ohms

ELECTRICAL PROPERTIES

With electrical continuity

ELECTROMAGNETIC IMMUNITY FOR VDM WIRING

Secured with the metal divider guide supplied in the column.

IP RATING

IP4X

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (ºC)

-25 to +120 ºC

VERSION

2 sides

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS
Only with tool

REMOVAL OF COVER
Only with tool

TYPE OF FASTENING
Using connecting pins

INSTALLATION DIRECTION
Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE
Suitable for installing in any floor type, raised or concrete. Column secured by applying pressure to the ceiling slab using a telescopic guide.

REMOVAL OF TRIM FRAMES
Only with tool

REGULATIONS

REGULATIONS
Directive 2014/35/UE LVD + EN 50085-2-4:2009

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053101896

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
2.31

PRODUCT NET WEIGHT
2.31

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053101896

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
3006

PACKAGING WIDTH
119

PACKAGING LENGTH
139

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
0.497

PACKAGING VOLUME UNIT
HLT

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
2.31

PACKAGING WEIGHT UNIT
KGM