

MD-36 High Ceilings PIR+LUX surface DALI-2 Input white IP54

REF. 89207338-230



BASIC INFORMATION

DESCRIPTION

Surface-mounted PIR motion and light detector. The recommended installation height is 12 m, with a maximum height of 14 m. It has a detection angle of 360° and an opening angle of 90°. The tangential detection range is 36 m and the radial detection range is 14 m.

The light regulation range is 2 - 1000 lux. The configuration of the detector is done via DALI.

Possibility of interconnection between sensors through DALI. The control protocol is DALI-2 Input. The typical consumption is 5 mA.

The power supply voltage is DALI (12 - 20.5 VDC). The operating temperature of the detector is: -20 - 50°C. White finish, protection degree IP 54 and dimensions: 95 x 95 x 65 mm.

5-year warranty

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

ETIM CLASS

EC001582

TECHNICAL INFORMATION

IP RATING

IP54

RAL

9003

POWER SUPPLY (V~)

DALI bus (12 Vdc – 20,5 Vdc)

CONTROL

DALI2 Slave

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

4

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053342091

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.242

PRODUCT NET WEIGHT

0.152

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053342091

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

90

PACKAGING WIDTH

124

PACKAGING LENGTH

160

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1785600

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.242

PACKAGING NET WEIGHT

0.152

PACKAGING WEIGHT UNIT

KGM