

## Complete kit with cover, brush, 4 schuko socket outlets and plate for 2 RJ45 connectors black S400 Indesk

REF. 44504020-138



### BASIC INFORMATION

#### DESCRIPTION

Simon offers us a complete kit integrated into the table with cover and brush, capacity for 4 schukos for standard power and a plate for 2 RJ45 connectors finished in black from the Simon 400 Indesk series. A piece with dimensions of 295 x 185 x 85 millimeters created to integrate perfectly into any space, thanks to its great design and manual lifting system. It features 4 bases for standard circuit power of 250 volts and 16 amperes. As with all Simon products, quality is guaranteed; this kit has a housing in painted steel, an anodized aluminum profile, covers and fasteners in self-extinguishing thermoplastic and halogen-free that ensure no flame propagation in case of fire and low toxicity in case of smoke emission.

#### FINISH

Black

#### MATERIAL

Metal

#### COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

#### PACKAGING CONTENTS

Pre-wired profile, enclosure, fastening claws and installation manual.

#### ETIM CLASS

EC002759

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

No

### PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the included protective cover and cable outlet with brush

### DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

### MAX TEMP DURING CONSTRUCTION WORK (°C)

+60°C

### FORMAT

Schuko

### HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

### IK CLASSIFICATION

07

### INSULATION RESISTANCE (V-MΩ)

>5 MΩ at 500 V

### CURRENT (A)

16 A

### IP RATING

IP30

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60°C

### NOMINAL VOLTAGE (V~)

250 V~

### OPERATING TEMPERATURE RANGE (°C)

-5...+60

### TYPE OF POWER SUPPLY CONNECTOR

Wieland GST 18i male 3-pole overhead connector with 22 cm patch cord

### RAL

9005

### RECESS DIMENSION (MM)

273 x 175 mm (± 2mm)

### NUMBER OF RJ45 WINDOWS

2

### SNAP-FIT RJ45 PLATES

Keystone I, II and Systimax

### SNAP-FIT TYPE

Keystone I, II and Systimax

### NUMBER OF SOCKETS

4 sockets for standard current circuit

### VERSION

5 elements

## INSTALLATION AND MAINTENANCE

### CABLING ACCESS

With brush

### CLAW RANGE OF OPERATION (MM)

Between 20 and 40 mm

### NUMBER OF COVER OPENING POSITIONS

1

### EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

### TYPE OF FASTENING

By tightening existing clamps in the fastening bracket.

### REMOVAL OF THE FRAME

Only with tool

### INSTALLATION TYPE

Suitable for recessed mount in furniture.

### OPENING ORIENTATION

At 45°

### SECURING POSSIBILITIES

Using supplied claws or screws in the available holes

### MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

## REGULATIONS

### REGULATIONS

Directiva 2014/35/UE LVD; Directiva 2011/65/UE RoHS; EN 50581:2012; EN 60670-1:2005; EN 60670-1:2005 A1:2013; IEC 60884-1 Ed 3.2;

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053208236

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING GROSS WEIGHT

1.95

### PRODUCT NET WEIGHT

1.95

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053208236

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

275

### PACKAGING WIDTH

195

### PACKAGING LENGTH

90

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

4826250

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0

### PACKAGING NET WEIGHT

1.95

### PACKAGING WEIGHT UNIT

KGM