Voice and data flat plate without dust cover and 1 element with 1 RJ45 connector category 6 FTP white Simon K45

REF. **K096F/9**



BASIC INFORMATION

DESCRIPTION

The plate of voice and data flat plate with 1 element without dust cover with RJ45 connector category 6 FTP within the collection Simon K45 with a cloth tone snow white, it fits perfectly into the set of a reduced space. With an average number of modules, it is composed of metal materials with thermoplastic isolated, halogen-free, which prevents the flame spread and toxicity smoke in case of fire. The plate of K45 voice and data of Simon, which supports cabling 22-24 AWG and ports type Keystone I and II, requires the use of 90 ° positioner in case of combining the K45 flat base plate in vertical enclosures to orient her position in the appropriate. Suitable for installation in recessed or surface-mounted, the RJ45 connector is clipped directly onto the plate without the need of screws, reducing installation time and maximizing its functionality, quality, elegance and innovation in the entire range Simon K45.

FINISH

White

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

Flat voice and data plate without dust cover, RJ45 category 6 FTP connector and installation manual

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90º positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
22-24 AWG wiring

RJ45 CONNECTION
With insertion tool

CONNECTOR CHARACTERISTICS
Category 6 FTP

RJ45 CONNECTORS
Included in voice and data plate

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60° C

DUST PROTECTION
No

FORMAT
RJ45

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60° C

NUMBER OF MODULES
Half

PLATE TYPE
Flat

RAL
9003

RJ45 ADAPTOR MODULE
Included in voice and data plate

SNAP-FIT RJ45 PLATES
Keystone I, II, ATT®/Avaya®

SNAP-FIT TYPE
Keystone I, II, ATT®/Avaya®

VERSION
Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

INSTALLATION DIRECTION
Vertical according to the direction of the mechanisms

INSTALLATION TYPE
Suitable for surface and flush mounting

REMOVAL OF THE PLATE
Only with tool

REGULATIONS

REGULATIONS
Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
211575

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.03

PRODUCT NET WEIGHT
0.03

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436031982

UNITS CONTAINED PACKAGING
10

PACKAGING HEIGHT
65

PACKAGING WIDTH
155

PACKAGING LENGTH
210

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
2115750

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.3

PACKAGING NET WEIGHT
0.3

PACKAGING WEIGHT UNIT
KGM