

Voice and data angled plate with dust cover for 1 element and 1 RJ45 connector category 6 UTP black Simon K45

REF. K8096U/14



BASIC INFORMATION

DESCRIPTION

With measures of 45x45 mm, the Simon K45 series presents its new plate of voice and data tilted plate with dust cover with 1 RJ45 connector category 6 UTP. The part presents an original finishes in black and is manufactured with metal components halogen-free that guarantees that is not the flame spread in case of fire and the low toxicity in case of smoke. You want to combine the voice and data plate in vertical enclosures, it is necessary to use the 90° positioner to be able to guide the piece in vertical position. And it is that the series Simon K45 offers the latest market innovations with the best quality and guarantee of the brand, without a doubt, it is the perfect solution for those who are looking for the best solutions of workplace solutions for your home.

FINISH

Black

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-038)

PACKAGING CONTENTS

Voice and data tilted plate with dust cover, direct module for snap-fit connector and RJ45 category 6 UTP connector

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90° positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

PLATE TYPE

Angled

CABLE SECTION ADMITTED (MM)

22-26 AWG wiring

FORMAT

RJ45

RAL

7021

RJ45 CONNECTION

With insertion tool

IP RATING

IP20

RJ45 ADAPTOR MODULE

Supplied with the voice and data plate

CONNECTOR CHARACTERISTICS

Category 6 UTP

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

MAX TEMP DURING

CONSTRUCTION WORK (°C)

+60° C

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

VERSION

Single

NUMBER OF MODULES

Half

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-038)

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

INSTALLATION TYPE

Suitable for surface and flush mounting

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.029

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

2871375

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436040274

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0.3

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0.26

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING HEIGHT

95

PACKAGING NET WEIGHT

0.29

UNITARY PACKAGING GROSS WEIGHT

0.029

PACKAGING WIDTH

155

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

195