Adjustable floor box kit for concrete floor 6 elements with 1 double socket,1 double UPS socket and 2 plates with 1 RJ45 Cat.6A FTP connector grey Simon 500 Cima

REF. **52007301-030**



BASIC INFORMATION

DESCRIPTION

From the Simon 500 Cima series comes this with adjustable floor box kit for concrete floor and 6 elements with 1 double socket, 1 double UPS socket and 2 plates with 1 RJ45 Cat.6A FTP connector. In the format French-Belgian socket and snap-fit RJ45 Keystone I, II, ATT ® / Avaya ®. Finished in grey, with 1 double socket for standard current circuit. When installing mounted, keep in mind that it has a click terminal connection (1 click ®). To complete a successful installation of this product, it must be combined with a plastic tray (reference 52052103-035). Optionally, we recommend combining it with the flush-mount trim cover (reference 52053103-035) in cases where you do not install the same floor covering. This kit is specially designed and designed for assembly in concrete floor, although it is also suitable for installation in raised floor. Manufactured with different metal materials that have properties self-extinguishing and halogen-free. In case of fire, you will get the maximum protection.

FINISH

Grey

COMPATIBILITY

Simon 500 CIMA mechanisms

MATERIAL

Plastic

ETIM CLASS

EC000024

REMARKS

To complete the installation of the product, it must be combined with a plastic tray (ref.52052103-035) or with a metal tray (ref.52052203-033). Alternatively, it may be combined with flush-mount trim cover (ref.52053103-035) in cases where the same floor lining is not installed.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS
Yes

NUMBER OF CLAMP-HOLDER HOLES
8

NUMBER OF CONNECTORS
2

CONNECTOR TYPE
6A FTP

DUST SHUTTER
Yes

FORMAT
French-Belgian

IK CLASSIFICATION
08

INDICATOR FUNCTION
Yes

CURRENT (A)
16 A

IP RATING
IP4X

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

PLATE TYPE
Flat

RAL
7011

RECESS DIMENSION (MM)
170 x 210 mm

NUMBER OF UPS SOCKET OUTLETS
1

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)
0

NUMBER OF COVER OPENING POSITIONS
2

EXTINGUISHING (°C)
+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

REMOVAL OF THE FRAME
Only with tool

CAN BE INSTALLED IN TRAY
Plastic and metallic

INSTALLATION DIRECTION
Horizontal, Vertical

REMOVAL OF THE PLATE
Only with tool

REMOVAL OF THE SOCKET
Only with tool

TYPE OF TERMINAL CONNECTION - FUNCTION 1
1 click connection (1 click®)

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053112304

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
1.85

PRODUCT NET WEIGHT
1.85

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053112304

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
75

PACKAGING WIDTH
200

PACKAGING LENGTH
230

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
3450000

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
1.85

PACKAGING WEIGHT UNIT
KGM