

Simon JR1 LED beacon luminaire, size S, made of die-cast aluminium with recessed beacon and high output

REF. 50-18618



BASIC INFORMATION

BODY MATERIAL

Die-cast aluminium

DIFFUSER MATERIAL

Flat, lenticular tempered glass

SUPPLY AND PACKAGING

Packed in recycled cardboard with an identifying label to protect the product during transport and storage.

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IK CLASSIFICATION

09

IP RATING

IP65

MAINTENANCE

Keep the diffuser surface clean to achieve maximum light flux. Use a damp rag without any type of harsh product or detergent. Lubricate the sealing gaskets and replace them when they are cracked. Lubricate the closures and/or hinges of the moving parts. Keep the thermal radiation surface clean to not lose light flux without shortening the life of the LEDs.

COLOR TEMPERATURE (K)

5600 K

LOCKING SYSTEM

With stainless steel screws

POWER FACTOR (Φ)

$\geq 0,95$

POWER (W)

7 W

RECYCLABILITY

Yes

SUPPLY CURRENT (mA)

30

SUPPLY VOLTAGE (VAC)

Input 220-240 VAC

REGULATIONS

ENEC+ CERTIFICATION

No

WARRANTY

5 years

REGULATIONS

EN 60598-2-5 / EN 62493 / EN 55015 / EN 61547 / EN 61000-3-2 / EN 50425

LOGISTICS INFORMATION

UNITARY EAN CODE

8431715056532

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0.013

UNITARY PACKAGING VOLUME
UNIT

MTQ

UNITARY PACKAGING GROSS
WEIGHT

3.25

PRODUCT NET WEIGHT

3.05

UNITARY PACKAGING WEIGHT
UNIT

KGM

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

0

PACKAGING WIDTH

0

PACKAGING LENGTH

0

PACKAGING VOLUME

0

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

3.05

PACKAGING WEIGHT UNIT

KGM