

Floodlight Pro 19,3W 3000K with detector 12m 240° PIR+LUX white IP44

REF. 89193000-203



BASIC INFORMATION

DESCRIPTION

Projector with PIR detector. The power is 19.3 W, the luminous flux is 2124 lm, and the color temperature is 3000 K. The maximum installation height is 4m, and the installation is on the wall (surface). The detection range is 12m, and the detection angle is 240°. The luminosity regulation range is 2 - 2000 lux, and the timing range is 10 s - 15 min. The configuration of the luminaire is done through potentiometers. The power supply voltage is 220 - 240 VAC. The operating temperature is: -20 - 40 °C. Protection grade IP 44 and IK 03, and dimensions: 161 x 180 x 223 mm. 5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

Black

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IP RATING

IP44

IK CLASSIFICATION

03

POWER SUPPLY (V~)

220/240 V~

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053400586

UNITARY PACKAGING GROSS WEIGHT

0.98

PACKAGING LENGTH

245

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.64

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

2325323

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053400586

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.98

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

225

PACKAGING NET WEIGHT

0.64

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

147

PACKAGING WEIGHT UNIT

KGM