

Flat voice and data plate with dust cover for 1 element with 2 RJ45 category 6 FTP graphite Simon 500 Cima

REF. 50003089-038



BASIC INFORMATION

DESCRIPTION

Flat base plate for voice and data in graphite colour of the Simon 500 Cima range with a dust cover with 1 element and 2 RJ45 category 6 FTP of the signature Keystone I, II, ATT ® / Avaya ®. Its installation is very simple and no vas to need any type of adapter for fastening in enclosures horizontal or vertical, as this plate includes the clips required. Designed according to the regulation TIA 568 C. 2, the Simon 500 Cima graphite plate has been manufactured with the best materials and safest: Metal components with self-extinguishing, halogen-free thermoplastic insulation. Thanks to these materials, it is not propagate the fire, in case of fire, and if had smoke, the levels toxic does not would be high. It measures 50 x 50 x 45,4 mm and can be installed perfectly in places where the temperature is located between the -5 and 60 ° C, approximately.

FINISH

Graphite

PACKAGING CONTENTS

Flat voice and data plate with dust cover, 2 RJ45 category 6 FTP and installation manual

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

PLATE TYPE

Flat

CABLE SECTION ADMITTED (MM)

22-26 AWG wiring

FORMAT

RJ45

RAL

7021

RJ45 CONNECTION

Without insertion tool

IP RATING

IP20

RJ45 ADAPTOR MODULE

Included in voice and data plate

CONNECTOR CHARACTERISTICS

category 6 FTP

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

NUMBER OF CONNECTORS

2

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

VERSION

Single

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

NUMBER OF MODULES

1

INSTALLATION AND MAINTENANCE

REMOVAL OF CONNECTOR

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053097892

PACKAGING VOLUME

0.052

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

20

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

80

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS
WEIGHT

0.056

PACKAGING WIDTH

224

PACKAGING NET WEIGHT

1.12

PRODUCT NET WEIGHT

0.056

PACKAGING LENGTH

290

PACKAGING WEIGHT UNIT

KGM

