# Customisable set with cover and brush, 4 schuko socket outlets and 1 empty element white S400 Indesk

REF. **44504000-130**



## BASIC INFORMATION

### DESCRIPTION

A piece created for flush mounting in the table and can be accessed in a simple way, thanks to its manual elevation system. This is a kit customizable with cover and brush strip, for 4 Schuko socket outlets and one empty element, made of metal has a finish is white in colour and belongs to the series Simon 400 Indesk. For a voltage of 250 volts and a current of 16 amps has a connector figure Wieland ® gst18i with 3 poles male in-line with patch cord of 22 cm and its dimensions are 295 x185 x85 millimetres. This piece stands out for its resistance to the knocks thanks to its enclosure painted steel, its profile in anodised aluminium. Another fundamental characteristic is its resistance to the fires, thanks to its covers and fastenings in self-extinguishing thermoplastic and halogen-free will avoid the propagation of the flame and the creation of fumes toxic.

### FINISH

White

### MATERIAL

Metal

### COMPATIBILITY

Functions of the Simon 400 range, combinable with the Simon Electric Cabling range.

### PACKAGING CONTENTS

Pre-wired profile, enclosure, fastening claws and installation manual.

### ETIM CLASS

EC002759

### REMARKS

To complete the product installation combine it with the Simon 400 functions (refs. 400XXXXX-03X).

# TECHNICAL INFORMATION

### AVAILABLE MARKET
CE

### PROTECTION AGAINST DIRECT ACCESS OF CONTACTS
No

### PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS
Yes, thanks to the included protective cover and cable outlet with brush

### DIELECTRIC STRENGTH
No holes or contours, with 2000V at 50 Hz for 1 minute

### MAX TEMP DURING CONSTRUCTION WORK (°C)
+60°C

### NUMBER OF POSSIBLE ELEMENTS
1

### FORMAT
Schuko

### HEAT RESISTANCE (°C)
+70°C (according to standard IEC 60670)

### INSULATION RESISTANCE (V-MΩ)
>5 M? at 500 V

### CURRENT (A)
16 A

### IP RATING
IP30

### MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 at +60° C

### NOMINAL VOLTAGE (V~)
250 V~

### TYPE OF POWER SUPPLY CONNECTOR
Wieland® GST 18i male 3-pole overhead connector with 22 cm patch cord

### RAL
9016

### NUMBER OF REAR ENTRANCES
1

### RECESS DIMENSION (MM)
273 x 175 mm (± 2mm)

### NUMBER OF SOCKETS
4 sockets for standard current circuit

### VERSION
5 elements

## INSTALLATION AND MAINTENANCE

### CABLING ACCESS
With brush

### CLAW RANGE OF OPERATION (MM)
Between 20 and 40 mm

### REMOVAL OF COMPONENTS

### NUMBER OF COVER OPENING POSITIONS
1

### EXTINGUISHING (ºC)
+70 ºC (according to standard IEC 60670)

### TYPE OF FASTENING
By lateral tightening of claws provided with the enclosure. Optional possibility to fasten the enclosure with screws through the provided holes in the sides of the enclosure chassis.

### REMOVAL OF THE FRAME
Only with tool

### INSTALLATION TYPE
Suitable for recessed mount in furniture.

### OPENING ORIENTATION
At 45

### REMOVAL OF THE PLATE
Only with tool

### SECURING POSSIBILITIES
Using supplied claws or screws in the available holes

### MOUNTING WITHOUT ACCESSORIES
Supplied with all necessary materials for installation.

## REGULATIONS

### REGULATIONS
Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

## LOGISTICS INFORMATION

UNITARY EAN CODE
8421053196458

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
2.135

PRODUCT NET WEIGHT
2.135

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053196458

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
320

PACKAGING WIDTH
195

PACKAGING LENGTH
90

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
5616000

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
2.135

PACKAGING WEIGHT UNIT
KGM