

Front kit for 1 element with 1 German socket outlet and built-in USB charger with smartcharge gloss white Simon 100

REF. 10020109-130



BASIC INFORMATION

DESCRIPTION

Front kit for 1 element, with 1 Schuko plug base and integrated USB charger. The device has a bright white finish, very characteristic of the Simon 100 series. The Schuko plug base has an intensity of 16 A, while the USB has an intensity of 2.1 A. The voltage it supports is 250 V. Very easy to install, it has a type of screw connection, everything is operated by a simple mechanism that works by pulsation. The device offers a USB plug and connector.

This kit has dimensions of 85.5x83.5mm. It can be installed both vertically and horizontally. To perform a correct maintenance of the device, a temperature range of 5 to 40° C must be preserved for its operation and a temperature range of -25 to 50° C for storage.

It has been developed following the regulations 2014/35 / UE LVD + directive 2014/30 / UE EMC + directive 2011/65 / UE RoHS + EN 60950-1: 2006 + A11: 2009 + A1: 2010 + A12: 2011 + A2 : 2011 IEC 60884-1 Ed. 3.2 ETSI-EN 301489-34 V1.4.1 EN 50581: 2012 and is marketed within the EC.

FINISH

Gloss white

COMPATIBILITY

Simon 100 mechanisms kit

ETIM CLASS

EC000007

MATERIAL

Thermoplastic

PACKAGING CONTENTS

Mechanism and instructions

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

IP RATING

IP20

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

NUMBER OF POSSIBLE ELEMENTS

1 element

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

FORMAT

Schuko,USB

VERSION

1 element

INDICATOR FUNCTION

No

MONOBLOCK

Yes

INSTALLATION AND MAINTENANCE

INSTALLATION DIRECTION

Horizontal, Vertical

INSTALLATION TYPE

Suitable for flush mounting

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2014/30/UE EMC + Directive 2011/65/UE RoHS + EN 60950-1:2006 + A11:2009 + A1:2010 + A12:2011 + A2:2011 IEC 60884-1 Ed. 3.2 ETSI-EN 301489-34 V1.4.1 EN 50581:2012

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053091111

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053091111

PACKAGING VOLUME

178516.8

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

25.3

PACKAGING GROSS WEIGHT

0.052

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

84

PACKAGING NET WEIGHT

0.052

UNITARY PACKAGING GROSS WEIGHT

0.052

PACKAGING LENGTH

84

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.052