

Spotlight 640.00 Rail Rose Wide Flood Black

REF. 64000038-481



BASIC INFORMATION

DESCRIPTION

Model for lighting Interior reference 64000038-481, design of spotlight with rail belonging to the range 640, compatible with other elements of the same helps to a lighting project. Stable, continuous and focused. It is an element 3-phase rail for lighting of different spaces and environments. Work professionals. Provides a type of lighting colour and a type of Rose WIDE FLOOD optics electrical control version. On-off with up to a value of power of 23 W. Element with 3-phase rail Category B, with dimensions of 100x102 Mm, ideal for small spaces and corner surfaces. Element with high aesthetics and colour, finishes and tone In black.

APPLICATION

Accent lighting, General lighting

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DIRECTIONAL

Yes

LUMENS (LM)

1700 lm

IP RATING

IP20

DRIVER INCLUDED

Yes

LUMENS/W

1700 lm/30W

OPERATING TEMPERATURE RANGE (°C)

35 °C maximum

ELECTRICAL CLASS

Type 1

OPTICS

Wide Flood

POWER SUPPLY (V~)

120/240 V~

L70 (°C)

100,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

COLOR TEMPERATURE (K)

1750 K

L90 (°C)

30,000 h at 25 °C

POWER (W)

30 W

CONTROL

On/Off

COLOR TYPE

Rose

SERVICE LIFE

50.000 h

LIGHTING EFFICIENCY (LM/W)

57 lm/W

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

3-phase rail

REGULATIONS

WARRANTY

5 years 50,000 h

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

1.574

PRODUCT NET WEIGHT

1.372

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053133309

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

230

PACKAGING WIDTH

130

PACKAGING LENGTH

180

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

5382000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

1.574

PACKAGING NET WEIGHT

1.372

PACKAGING WEIGHT UNIT

KGM