

Thermostat gloss black Simon 100

REF. 10000810-138



BASIC INFORMATION

FINISH

Gloss black

PACKAGING CONTENTS

Mechanism and instructions

ETIM CLASS

EC003263

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

NUMBER OF POSSIBLE ELEMENTS

1 element

FORMAT

Clima

INDICATOR FUNCTION

No

CURRENT (A)

5 A

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TYPE OF MECHANISM

Touch

MONOBLOCK

Yes

OPERATING TEMPERATURE RANGE (°C)

0 - 40 °C

STORAGE TEMPERATURE RANGE (°C)

-25 - 75 °C

VERSION

Unique

VOLTAGE (V~)

127/230 V~

INSTALLATION AND MAINTENANCE

CLAW

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

universal

INSTALLATION DIRECTION

Horizontal, Vertical

INSTALLATION TYPE

Suitable for flush mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053201770

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053201770

PACKAGING VOLUME

1000125

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

75

PACKAGING GROSS WEIGHT

0.287

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

105

PACKAGING NET WEIGHT

0.287

UNITARY PACKAGING GROSS
WEIGHT

0.287

PACKAGING LENGTH

127

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT


0.287



Instalación centralizada para caldera/bomba de calor
Centralized installation for boiler/heat pump



Instalación suelo radiante eléctrico
Installation with electric floor



Instalación zonificada a 230V con contacto Normalmente Abierto
230V installation with Normally Open contact

Para información más detallada consultar la hoja de instrucciones
For more detailed information check the instruction sheet