

Luminaire P2-Flat 15,1W 3000K with detector 8m HF+LUX IP54

REF. 89191000-153



BASIC INFORMATION

DESCRIPTION

Luminaire with integrated HF detector, power 15.1 W, luminous flux of 1700 lm and color temperature of 3000 K. The maximum installation height is 4m and the installation is on the surface. The detection range is 8m and the detection angle is 360°. The dimming range is 2 - 2000 lux and the timing range is 5 s - 15 min. Allows for interconnection of master/master and master/slave luminaires. The power supply voltage is 220 - 240 VAC. The operating temperature is: -10 - 40 °C. Protection grade IP 54 and IK 3 and dimensions: Ø 322 x 68 mm. 5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IP RATING

IP54

POWER SUPPLY (V~)

220/240 V~

IK CLASSIFICATION

03

MAXIMUM POWER (W)

400

CONTROL

On/Off

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053341605

UNITARY PACKAGING GROSS WEIGHT

1.113

PACKAGING LENGTH

370

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.613

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

20535000

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053341605

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

1.113

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

370

PACKAGING NET WEIGHT

0.613

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

150

PACKAGING WEIGHT UNIT

KGM