

German socket outlet 16A 250V~ with safety device and fast terminal connection white Simon 27 Play

REF. 27432-65



BASIC INFORMATION

DESCRIPTION

Quality at the best price. This is how we could define the Socket-outlet with lateral Schuko ground connection, with 16A current and 250V~ voltage and white fast-terminals connection of the Simon 27 Play series (45x45 mm) includes a safety device that makes it perfect for rooms with minors in which we want to avoid any type of unexpected accident, as the covers include the child protection function. It is ideal to assemble in new work or to replace in reforms carried out in certain rooms of a home or a company, its installation is carried out by means of insertion, making it the most popular choice for use in offices, hotels, health centres, educational centres or commercial establishments. The metal components with halogen-free thermoplastic insulation and thermo-stable trim with which it has been manufactured stand out for their durability and resistance to the adverse elements of the ambience in which it is located.

FINISH

White

COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

PACKAGING CONTENTS

Socket outlet with cover

ETIM CLASS

EC000125

REMARKS

The covers include a child-proof protective feature.

TECHNICAL INFORMATION

AVAILABLE MARKET CE	CURRENT (A) 16 A	MONOBLOCK No
CABLE SECTION ADMITTED (MM) 2,5 mm	IP RATING IP20	OPERATING TEMPERATURE RANGE (°C) 5 - 40 °C
NUMBER OF POSSIBLE ELEMENTS 1 element	MAINTENANCE Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.	STORAGE TEMPERATURE RANGE (°C) -25 - 50 °C
FORMAT Schuko	TYPE OF MECHANISM Insertion	VERSION Single
INDICATOR FUNCTION No		VOLTAGE (V~) 250 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM) 15	INSTALLABLE IN FLUSH MOUNT JUNCTION BOX Universal, American and Centralisations	INSTALLATION TYPE Suitable for surface and flush mounting
CLAW Simon 27	INSTALLATION DIRECTION Horizontal, Vertical	TYPE OF TERMINAL CONNECTION - FUNCTION 1 Fast

REGULATIONS

REGULATIONS

Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | UNE 20315-1-1:2017 | IEC 60884-1 Ed 3.2 | UNE 20315-1-2:2017

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053252093

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.054

PRODUCT NET WEIGHT

0.054

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053051504

UNITS CONTAINED PACKAGING

10

PACKAGING HEIGHT

53

PACKAGING WIDTH

105

PACKAGING LENGTH

221

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1229865

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.54

PACKAGING NET WEIGHT

0.54

PACKAGING WEIGHT UNIT

KGM