

Push-button switch with light symbol 10A 250V~ and fast terminal connection system champagne Simon 31

REF. 31651-34



BASIC INFORMATION

DESCRIPTION

In our section for control mechanisms, you can also find Push Button of the Simon 31 series, which has different models, some more classic but also other ideal for the most modern. In front of you is this push-button switch with engraved light that supports elements of 10 Amps and 250 Volt voltage, with a quick terminal connection system and a magnificent and stylish champagne finish. 1 element and the number of modules is 2. The engraving in light is ideal for handling the mechanism in the dark. In addition to the champagne finish, in our online catalogue you will find more options: Up to 5 finishes available to choose the one that best suits what you are looking for, although we always recommend choosing the frame in the same colour as the rocker or cover that you have selected. Section of wire cross-section of 1.5 to 2.5 millimetres and stripping of 11 millimetres. It measures 64 by 65 millimetres. The manufacturing materials used are metal elements with halogen-free insulation and, on the other hand, metallised thermoplastic trim. Another product of the highest quality brand Simon.

FINISH

Champagne

PACKAGING CONTENTS

Mechanism with rocker

COMPATIBILITY

Simon 31 frames

ETIM CLASS

EC000029

REMARKS

Available in 5 finishes. It is recommended to choose a frame the same colour as the selected rocker.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CURRENT (A)

10 AX

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

IP RATING

IP20

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

NUMBER OF POSSIBLE ELEMENTS

1 element

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VERSION

Single

INDICATOR FUNCTION

No

TYPE OF MECHANISM

Pivoting

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

11

INSTALLATION TYPE

Suitable for surface and flush mounting

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Fast

REGULATIONS

REGULATIONS

UNE-EN 60669-1:2002 + A1:2003 + A2:2009

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053009154

PACKAGING VOLUME

3026595

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

10

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

83

PACKAGING GROSS WEIGHT

0.895

UNITARY PACKAGING GROSS WEIGHT

0.09

PACKAGING WIDTH

165

PACKAGING NET WEIGHT

0.9

PRODUCT NET WEIGHT

0.09

PACKAGING LENGTH

221

PACKAGING WEIGHT UNIT

KGM