

Aluminum trunking of 2m 160x55mm with 2 compartments for K45 functions

REF. TK11122/8



BASIC INFORMATION

DESCRIPTION

Aluminum channel with a length of 2m and a section of 165x55mm, featuring 2 front compartments capable of mounting all functions of the K45 range without the need for accessories, resulting in significant time savings during assembly. Regardless of the designed structure, it ensures the isolation of electrical wiring from voice, data, and multimedia, as well as maintaining its correct bending radius throughout the distribution. It adapts to various architectures through its installation accessories, with the possibility of branching to Mini-channel and Cable guide via the pre-stamped line. Made of high-quality anodized aluminum, it is equipped with an IP4X and IK07 protection rating. We are talking about a fireproof material, self-extinguishing, and non-flame propagating. The indicated price is per meter and is supplied in batches of 4 units (8 meters in total)

FINISH

Aluminium

COMPATIBILITY

Functions K45

MATERIAL

Aluminium

ETIM CLASS

EC001938

TECHNICAL INFORMATION

IK CLASSIFICATION

09

IP RATING

IP4X

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

REMOVAL OF COVER

No tools needed

REMOVAL OF THE FRAME

Only with tool

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053264225

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0

PRODUCT NET WEIGHT

2.5

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8426436027916

UNITS CONTAINED PACKAGING

8

PACKAGING HEIGHT

190

PACKAGING WIDTH

157

PACKAGING LENGTH

2020

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

60256600

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

20

PACKAGING NET WEIGHT

20

PACKAGING WEIGHT UNIT

KGM