

Cover for mechanism-holder unit IP66 brass Simon K45

REF. RKS001/71



BASIC INFORMATION

DESCRIPTION

Cover for unit mechanism-holders brass IP66 in the series Simon K45 and that is perfect to be recessed in any type of floor, be it a raised or concrete. It has a diameter of 100 mm x 36 mm and it is only the replacement of a hinged cover to order as substitution for the existing and does not include the unit mechanism-holders. It is manufactured in thermoplastic baseboard brass on self-extinguishing halogen-free and, which is a material very safe and that guarantees no flame spread in case of fire and low toxicity in the event of a fire or that exist smoke. It has been designed according to the regulation UNE-EN 60.670-23 and can be installed in rooms with a temperature located between -25 to 60 ° C To clean this cover, just vas to need to use a soft and dry cloth and forget you to use any type of a cloth and / or abrasive cleaner containing chlorine in its formula.

FINISH

Brass

PACKAGING CONTENTS

Cover for brass IP66 mechanism-holder unit

ETIM CLASS

EC001903

MATERIAL

Metal

REMARKS

Replacement for hinged cover to order as substitution for the existing one (does not include mechanism-holder unit)

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, when the mechanism-holder unit is not in use, the cover can be hermetically sealed.

DIELECTRIC STRENGTH

Without perforation or contournement with 2000 V at 50H during 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+90° C

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

IK CLASSIFICATION

07,08

INSULATION RESISTANCE (V-MΩ)

>5 MOhm at 500 V

IP RATING

IP66

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-25 a 60° C

INSTALLATION AND MAINTENANCE

NUMBER OF COVER OPENING POSITIONS

1

REMOVAL OF COVER

Only with tool

EXTINGUISHING (°C)

+650 °C (according to standard IEC 60670)

TYPE OF FASTENING

By unscrewing from the mechanism-holder unit, removal of the frame and deteriorated cover, and replacement with the new cover.

INSTALLATION DIRECTION

The cover has a hinge to keep it rigid under the frame of the mechanism-holder unit.

INSTALLATION TYPE

Product intended as a spare part for the cover of the brass finished mechanism-holder unit (the reference does not include the frame or the mechanism-holder unit).

REGULATIONS

REGULATIONS

UNE-EN 60.670-23

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436056374

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8426436056374

PACKAGING VOLUME

0.864

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

40

PACKAGING GROSS WEIGHT

0.13

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

180

PACKAGING NET WEIGHT

0.13

UNITARY PACKAGING GROSS
WEIGHT

0.13

PACKAGING LENGTH

120

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.13