

## Movement detector switch from 40 to 300W/VA 230 V~ white Simon 82

REF. 82340-30



### BASIC INFORMATION

#### FINISH

White

#### COMPATIBILITY

Simon 75, Simon 82 Detail,  
Simon 82 Nature and Simon 82  
frames

#### COMPATIBLE WITH MECHANICAL PUSH BUTTON

Yes

#### COMPATIBLE WITH MECHANICAL SWITCH

No

#### PACKAGING CONTENTS

Movement detector and  
instruction sheet

#### ETIM CLASS

EC000133

#### REMARKS

Allows 2 units to be installed in parallel.

## TECHNICAL INFORMATION

|                                                                |                                                                                                               |                                     |
|----------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------|-------------------------------------|
| AVAILABLE MARKET<br>CE                                         | COMPATIBLE WITH<br>FLUORESCENT LAMPS WITH 1-<br>10V DIMMABLE ELECTRONIC<br>BALLAST                            | MAXIMUM QUANTITY PER<br>CIRCUIT     |
|                                                                | No                                                                                                            | 2                                   |
| CABLE SECTION ADMITTED (MM)                                    |                                                                                                               | TYPE OF MECHANISM                   |
| From 1,5 to 2,5 mm                                             |                                                                                                               | Detection                           |
| NUMBER OF CONTACTS                                             | COMPATIBLE WITH<br>FLUORESCENT LAMPS (VA)                                                                     | COMPATIBLE WITH MOTORS (VA)         |
| 3                                                              | No                                                                                                            | No                                  |
| NUMBER OF CONTROLLABLE<br>CIRCUITS                             | FREQUENCY                                                                                                     | OPERATING TEMPERATURE<br>RANGE (°C) |
| 1                                                              | 50 - 60 Hz                                                                                                    | 0 - 35 °C                           |
| DISCONNECTION TIMER                                            | INDICATOR FUNCTION                                                                                            | POWER SUPPLY (V~)                   |
| 4 seconds to 10 minutes                                        | Yes                                                                                                           | 230 V~                              |
| COMPATIBLE WITH HALOGENS<br>WITH ELECTRONIC<br>TRANSFORMER (W) | IP RATING                                                                                                     | APPROXIMATE RANGE (M)               |
| No                                                             | IP20                                                                                                          | 6 m                                 |
| NUMBER OF POSSIBLE<br>ELEMENTS                                 | COMPATIBLE WITH LOW<br>CONSUMPTION (W)                                                                        | STORAGE TEMPERATURE RANGE<br>(°C)   |
| 1 element                                                      | No                                                                                                            | 20 - 70 °C                          |
|                                                                | MAINTENANCE                                                                                                   | VERSION                             |
|                                                                | Clean with a soft, dry cloth. Do<br>not use abrasive cloths or<br>cleaning products that contain<br>chlorine. | Single                              |
|                                                                |                                                                                                               | NUMBER OF WIRES                     |
|                                                                |                                                                                                               | 2                                   |

## INSTALLATION AND MAINTENANCE

|                                               |                                   |                                            |
|-----------------------------------------------|-----------------------------------|--------------------------------------------|
| BUS CONNECTION TYPE OF<br>TERMINAL CONNECTION | CABLE STRIPPING NECESSARY<br>(MM) | INSTALLATION TYPE                          |
| Por inserción                                 | 8                                 | Suitable for surface and flush<br>mounting |
|                                               | INSTALLATION DIRECTION            |                                            |
|                                               | Horizontal, Vertical              |                                            |

## REGULATIONS

### REGULATIONS

UNE-EN-60669-2-1:2005+A1:2010+A12:2011

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053053447

### UNITARY PACKAGING HEIGHT

70

### UNITARY PACKAGING WIDTH

70

### UNITARY PACKAGING LENGTH

70

### UNITARY PACKAGING MEASUREMENT UNIT

MMT

### UNITARY PACKAGING VOLUME

0.343

### UNITARY PACKAGING VOLUME UNIT

DMQ

### UNITARY PACKAGING GROSS WEIGHT

0.197

### PRODUCT NET WEIGHT

0.16

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053053447

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

81

### PACKAGING WIDTH

81

### PACKAGING LENGTH

81

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

0.531

### PACKAGING VOLUME UNIT

DMQ

### PACKAGING GROSS WEIGHT

0.198

### PACKAGING NET WEIGHT

0.16

### PACKAGING WEIGHT UNIT

KGM