


Intermediate push-button switch 10AX 230V~ with slender rocker and fast terminal connection system titanium Simon 270

REF. 20001251-096



BASIC INFORMATION

FINISH

Matt titanium

MATERIAL

Thermoplastic

PACKAGING CONTENTS

Mechanism, cover and instruction sheet

TYPE OF ROCKER

Slender

COMPATIBILITY

Simon 270 frames

ETIM CLASS

EC001590

TECHNICAL INFORMATION

AVAILABLE MARKET CE	INDICATOR FUNCTION No	NOMINAL VOLTAGE (V~) 230 V~
CABLE SECTION ADMITTED (MM) From 1,5 to 2,5 mm	CURRENT (A) 10 AX	OPERATING TEMPERATURE RANGE (°C) 5 - 45 °C
TYPE OF COVER Slender	IP RATING IP20	POWER SUPPLY (V~) 230 V~
NUMBER OF POSSIBLE ELEMENTS Half element	MAINTENANCE Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.	RAL 9007
FORMAT Push-button	TYPE OF MECHANISM Pivoting	STORAGE TEMPERATURE RANGE (°C) -25 - 75 °C
FREQUENCY 50 - 60 Hz		VOLTAGE (V~) 127/230 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM) 15	INSTALLABLE IN FLUSH MOUNT JUNCTION BOX Universal	INSTALLATION TYPE Suitable for flush mounting
	INSTALLATION DIRECTION Horizontal, Vertical	TYPE OF TERMINAL CONNECTION - FUNCTION 1 Fast

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN 60669-1:2018 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053269664

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.03

PRODUCT NET WEIGHT

0.03

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053269671

UNITS CONTAINED PACKAGING

10

PACKAGING HEIGHT

47.75

PACKAGING WIDTH

57

PACKAGING LENGTH

262

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

713098.5

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

0.3

PACKAGING WEIGHT UNIT

GRM

