

**Flat voice and data plate without dust cover for 1 RJ45
R&M® (Reichle de Massari®) for 1 element graphite Simon
500 Cima**

REF. 50020185-038



BASIC INFORMATION

DESCRIPTION

With a structure made with halogen-free thermoplastic material, a component that guarantees no flame spread in case of fire and low toxicity in case of smoke, the Plate for voice and data plate without dust cover for a R&M (Reichle de Massari) RJ45 connector for one element in graphite finish is one of the most popular accessories in the Simon 500 Cima series. The security in electrical and electronic installations is assured with this plate of vos and data of 50 x 50 x 11 mm your design lines that stands out for its avant-garde criterion all types of decorations, both classic and modern. Also, this plate has clips for fastening in vertical and horizontal enclosures without the need for an adaptor. Its competitive price makes it affordable to all types of budgets.

FINISH

Graphite

PACKAGING CONTENTS

Flat voice and data plate without dust cover

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

No

NUMBER OF MODULES

1

AVAILABLE IN

Plate for 1 RJ45

DUST SHUTTER

No

PLATE TYPE

Flat

COMPATIBLE WITH CONNECTORS

Classic series Cat5e (R925371, R925370), Star Cat6 series (R302373, R302372) and Advanced Cat6A series (R509500, R509504) from R&M® (Reichle de Massari®).

FORMAT

RJ45

RAL

7021

IP RATING

IP20

RJ45 ADAPTOR MODULE

Included in voice and data plate

KIT AVAILABILITY

No

SNAP-FIT RJ45 PLATES

RJ45 R&M® connectors

RJ45 CONNECTORS

Not included in voice and data plate

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT TYPE

RJ45 R&M® connectors

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

VERSION

Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053097229

PACKAGING VOLUME

0.604

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

10

PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

54

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS WEIGHT

0.015

PACKAGING WIDTH

52

PACKAGING NET WEIGHT

0.15

PRODUCT NET WEIGHT

0.015

PACKAGING LENGTH

215

PACKAGING WEIGHT UNIT

KGM

