


2-way switch/push button with key 5A 250V~ (key removable in rest position) and welding terminal connection system

REF. 75520-39



BASIC INFORMATION

DESCRIPTION

Security, functionality and design within the 2-way switch / push-button switch of the Simon 75 collection. Colours the latest technology in lighting and the latest trends in decoration, the Simon 75 range is to each space, the specific finishes to allow the integration of the set in all kinds of environments. This 2-way switch / push-button switch is 1 mechanism equipped with 2 positions and a key blade that can be removed in the idle, with which you will obtain the maximum security in the minimum space compact. With a power of 250 Volt voltage and 5 Ampere current with amplitude modulated (5: 00 AM), supports a cable section of 0.5 mm Made of metal materials with halogen-free thermoplastic isolated, it offers a greater security against fire, reaching maximum temperatures of -25 to 50 °C. Designed for installation both recessed and surface-mounted, requires terminal connection by welding to complete the assembly and be fully in the specific space.

COMPATIBILITY

Simon 28, Simon 75, Simon 82
Detail, Simon 82 Nature, Simon
82 and Simon 88 frames

PACKAGING CONTENTS

Mechanism

REMARKS

Mechanism with 2 positions and removable key in rest position.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CURRENT (A)

5 A

NOMINAL VOLTAGE (V~)

250 V~

CABLE SECTION ADMITTED (MM)

0,5 mm

IP RATING

IP20

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

NUMBER OF POSSIBLE ELEMENTS

1 element

KEY-REMOVAL POSITION

Standby

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

INDICATOR FUNCTION

No

TYPE OF MECHANISM

Key

VERSION

Single

INSTALLATION AND MAINTENANCE

CLAW

Included

INSTALLATION TYPE

Suitable for surface and flush mounting

TYPE OF TERMINAL

CONNECTION - FUNCTION 1

Welding

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2011/65/UE RoHS + + EN 61058:2002 + EN 61058:2002 A2:2008 + EN 61058-2-1:2011

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053004814

PRODUCT NET WEIGHT

0.085

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

329232

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053004814

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.085

UNITARY PACKAGING VOLUME

329232

PACKAGING HEIGHT

57

PACKAGING NET WEIGHT

0.085

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

76

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

0.085

PACKAGING LENGTH

76