

# Complete kit with 4 schuko socket outlets and plate for 2 RJ45 connectors white S400 Top

REF. 42504020-130



## BASIC INFORMATION

### DESCRIPTION

Provide the perfect balance between design and functionality with the kit of desk top of Simon 400 Top. Designed to optimise the space and to win in quality, this kit consists of 4 Schuko socket outlets and a plate with 2 RJ45 connectors, compatible with Keystone I and II ports, ideal for work spaces with a high influx of people. Finishes in white and with a compact dimension, the kit is installed by flush mounted in furniture, connected to a figure Wieland gst 18i. Compatible with power supplies of 250 Volts, and 16 Ampere current, its dielectric strength is 2000 V at 50H per minute and has a insulation resistance > 5 M $\Omega$  at 500 V. Made of thermoplastic and anodised aluminium, protects the room in case of fire, and can reach maximum temperatures of more than 60  $^{\circ}$ C. Security, innovation and maximum functionality with the kit of desk top Simon 400 Top.

### FINISH

White

### MATERIAL

Metal

### COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

### PACKAGING CONTENTS

Pre-wired profile, table-top supports, rear trim cover and installation manual.

### ETIM CLASS

EC002759

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

### MAX TEMP DURING CONSTRUCTION WORK (°C)

+60°C

### FORMAT

Schuko

### HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

### IK CLASSIFICATION

07

### INSULATION RESISTANCE (V-MΩ)

>5 MΩ at 500 V

### CURRENT (A)

16 A

### IP RATING

IP30

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60°C

### NOMINAL VOLTAGE (V~)

250 V~

### OPERATING TEMPERATURE RANGE (°C)

-5...+60

### TYPE OF POWER SUPPLY CONNECTOR

Wieland GST 18i male 3-pole overhead connector with 22 cm patch cord

### RAL

9016

### NUMBER OF RJ45 WINDOWS

2

### SNAP-FIT RJ45 PLATES

Keystone I, II and Systimax

### SNAP-FIT TYPE

Keystone I, II and Systimax

### NUMBER OF SOCKETS

4 sockets for standard current circuit

### VERSION

5 elements

## INSTALLATION AND MAINTENANCE

### CLAW RANGE OF OPERATION (MM)

Between 16 and 40 mm

### TYPE OF FASTENING

By tightening existing clamps in the fastening bracket.

### SECURING POSSIBILITIES

Using clips included in the fastening brackets

### EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

### INSTALLATION TYPE

Suitable for fixing to furniture.

### MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

## REGULATIONS

### REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50173-1:2011;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053195895

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING GROSS WEIGHT

0.95

### PRODUCT NET WEIGHT

0.95

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053195895

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

90

### PACKAGING WIDTH

116

### PACKAGING LENGTH

298

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

3111120

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0

### PACKAGING NET WEIGHT

0.95

### PACKAGING WEIGHT UNIT

KGM