

Single-pole push-button switch 16AX 230V~ with fast terminal connection system matt black Simon 270

REF. 20000111-098



BASIC INFORMATION

FINISH

Matt black

COMPATIBILITY

Simon 270 frames

MATERIAL

Thermoplastic

ETIM CLASS

EC001590

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

INDICATOR FUNCTION

No

RAL

9005

CABLE SECTION ADMITTED (MM)

1.5 - 2.5

CURRENT (A)

16 AX

RECESS DIMENSION (MM)

40

NUMBER OF CONTACTS

2

IP RATING

IP20

VOLTAGE (V~)

127/230 V~

NUMBER OF POSSIBLE ELEMENTS

1

NOMINAL VOLTAGE (V~)

230 V~

NUMBER OF WIRES

2

FORMAT

Push-button

OPERATING TEMPERATURE RANGE (°C)

5 - 45 °C

FREQUENCY

50 - 60 Hz

POWER SUPPLY (V~)

230 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

15

REMOVAL OF COVER

Only with tool

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

CLAW

Simon 27

INSTALLATION DIRECTION

Horizontal, Vertical

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN 60669-1:2018 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053308523

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053308530

PACKAGING VOLUME

713098.5

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

5

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

47.75

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

57

PACKAGING NET WEIGHT

0.005

UNITARY PACKAGING GROSS
WEIGHT

0.001

PACKAGING LENGTH

262

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.001

