

Modular Luminaire 720 Advance M4 120x30 Low Glare BIO DALI DT6

REF. 72061340-686



BASIC INFORMATION

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LUMENS/W

4000 lm/ 34 W

IP RATING

IP44

INTEGRATED POWER SUPPLY

Yes

OPTICS

Microprismatic

OPERATING TEMPERATURE RANGE (°C)

40 °C maximum

L70 (°C)

100,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

POWER SUPPLY (V~)

100/240 V~

L90 (°C)

40,000 h at 25 °C

POWER (W)

34 W

COLOR TEMPERATURE (K)

2700 K - 5700 K

LIGHT BEAM APERTURE ANGLE (°)

100°

SERVICE LIFE

50.000 h

CONTROL

DALI

LIGHTING EFFICIENCY (LM/W)

118 lm/W

CRI

85

LUMENS (LM)

4000 lm

CHROMATICS CRI ICONS

CRI
82

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Plaster ceiling, surface mount, concealed or semi-concealed profile.

INSTALLATION TYPE

False ceiling, visible hardware

REGULATIONS

WARRANTY

5 years

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053091272

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

5.62

PRODUCT NET WEIGHT

5

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053091272

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

65

PACKAGING WIDTH

300

PACKAGING LENGTH

1200

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

23400000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

5

PACKAGING WEIGHT UNIT

KGM