

Wall luminaire L 840 BT Mesh 7W 3000K with detector 5m 160° HF+LUX IP44 3Y

REF. 89325602-693



BASIC INFORMATION

DESCRIPTION

Wall-mounted fixture with HF sensor and Bluetooth connectivity. The power is 9.1 W, the luminous flux is 319 lm, and the color temperature is 3000 K. The maximum installation height is 4m and the installation is wall-mounted (surface). The detection range is 5m and the detection angle is 160 °. The brightness regulation range is 2 - 2000 lux and the timing range is 5 s - 60 min. The configuration of the luminaire is done via a Bluetooth application. Possibility of interconnection between luminaires via Bluetooth mesh. The power supply voltage is 220 - 240 VAC. The operating temperature is: -20 - 40 °C. Protection grade IP 44 and IK 03, and dimensions: 134 x 110 x 110 mm. 3-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

Anthracite

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IP RATING

IP44

IK CLASSIFICATION

03

POWER SUPPLY (V~)

220/240 V~

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053400326

UNITARY PACKAGING GROSS WEIGHT

0.7

PACKAGING LENGTH

184

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.48

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

2325323

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053400326

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.7

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

184

PACKAGING NET WEIGHT

0.48

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

184

PACKAGING WEIGHT UNIT

KGM