

Flat voice and data plate with dust cover for 1 RJ45 Panduit® for 1 element graphite Simon 500 Cima

REF. 50019085-038



BASIC INFORMATION

DESCRIPTION

Plate with the voice and flat data plate of the Simon 500 Cima with dust cover for an RJ45 connector Panduit you will get the most speed in the transmission of data on the work area. With finishes in Graphite and the versatility of being able to be installed, thanks to its direct snap-fit, in horizontal or vertical enclosures, gives a total integration of the set in spaces compact giving a bonus of elegance and simplicity to the specific room. Manufactured with thermoplastic materials asylum seekers with halogen-free, protects your room of the flame spread and toxicity by smoke in case of fire. With the compatibility of RJ45 connectors of the range Panduit, accepted cabling 22-26 AWG and allows integration in the same enclosure of electrical, voice, data and multimedia, command and control innovation, quality and functionality as guarantee, within the flat base plate of voice and data Simon 500 Cima with RJ45 connector Panduit.

FINISH

Graphite

PACKAGING CONTENTS

Flat voice and data plate with
dust cover

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST SHUTTER

Yes

NUMBER OF MODULES

1

AVAILABLE IN

Plate for 1 and 2 RJ45

FORMAT

RJ45

PLATE TYPE

Flat

COMPATIBLE WITH CONNECTORS

Panduit® Mini-Com Series.

IP RATING

IP20

RAL

7021

RJ45 CONNECTORS

Not included in voice and data plate

KIT AVAILABILITY

No

RJ45 ADAPTOR MODULE

Included in voice and data plate

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

RJ45 Panduit® connectors

SNAP-FIT TYPE

RJ45 Panduit® connectors

DUST PROTECTION

Yes

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

VERSION

Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053097137

PACKAGING VOLUME

0.604

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

10

PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

54

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS
WEIGHT

0.026

PACKAGING WIDTH

52

PACKAGING NET WEIGHT

0.26

PRODUCT NET WEIGHT

0.026

PACKAGING LENGTH

215

PACKAGING WEIGHT UNIT

KGM

