

30 mA differential with 1 double element trim plate and 42 mm height graphite Simon Cima

REF. S195DS/14



BASIC INFORMATION

FINISH

Graphite

COMPATIBILITY

With Simon Cima Pro surface-mounted and flush-mounted wall boxes, Cima Classic flush-mounted wall boxes with a 33mm housing, adjustable shallow floor boxes, and PVC cable guide trunking.

ETIM CLASS

EC000042

TECHNICAL INFORMATION

BREAKING CAPACITY (A)

10000 A (with fuse in front)

KIT AVAILABILITY

No

POWER SUPPLY (V~)

125/230 V~

CURRENT (A)

30 mA

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

RAL

7021

IP RATING

IP20

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

10

INSTALLATION DIRECTION

Horizontal, Vertical

REMOVAL OF THE MCB

Only with tool

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436041059

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

753878

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.287

PRODUCT NET WEIGHT

0.287

UNITARY PACKAGING WEIGHT UNIT

KGM

UNITS CONTAINED PACKAGING

5

PACKAGING HEIGHT

118

PACKAGING WIDTH

121

PACKAGING LENGTH

264

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

3769392

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

1.435

PACKAGING NET WEIGHT

1.435

PACKAGING WEIGHT UNIT

KGM